

LC1F1400

TeSys F contactor - 3P(3 NO)-AC-1 \leq 1000 V
AC 1400 A with coil LX1/ LX9 - 110...500V AC
40/400Hz, LX4 - 110...440V DC



Product availability: Non-Stock - Not normally stocked in distribution facility



Main

Range	TeSys
Product name	TeSys F
Product or component type	Contacteur
Device short name	LC1F
Contacteur application	Resistive load
Utilisation category	AC-1
Poles description	3P
Power pole contact composition	3 NO
[Ue] rated operational voltage	\leq 1000 V AC 50/60 Hz \leq 460 V DC
[Ie] rated operational current	1400 A 104 °F (40 °C) \leq 440 V AC AC-1

Complementary

[Uc] control circuit voltage	100...500 V AC 40...400 Hz with LX1/LX9 coil 110...440 V DC with LX4 coil
[Uimp] rated impulse withstand voltage	8 kV
Overvoltage category	III
[Ith] conventional free air thermal current	1400 A 104 °F (40 °C)
Irms rated making capacity	2100 A AC IEC 60947-4-1
Rated breaking capacity	2100 A IEC 60947-4-1
[Icw] rated short-time withstand current	8000 A 104 °F (40 °C) - 10 s 6000 A 104 °F (40 °C) - 30 s 4500 A 104 °F (40 °C) - 1 min 4000 A 104 °F (40 °C) - 3 min 2600 A 104 °F (40 °C) - 10 min
Associated fuse rating	1600 A gG \leq 440 V IEC 60947-4-1
Average impedance	0.1 mOhm - Ith 1400 A 50 Hz
[Ui] rated insulation voltage	1000 V IEC 60947-4-1 1500 V VDE 0110 group C
Power dissipation per pole	150 W AC-1
Control circuit voltage limits	Operational 0.85...1.1 Uc AC 40...400 Hz Drop-out 0.3...0.5 Uc AC 40...400 Hz Operational 0.85...1.1 Uc DC Drop-out 0.2...0.35 Uc DC
Heat dissipation	18 W
Operating time	40...50 ms closing with LX1/LX9 coil 100...170 ms opening with LX1/LX9 coil 50...60 ms closing with LX4 coil 40...50 ms opening with LX4 coil
Mounting support	Plate
Standards	EN 60947-4-1 IEC 60947-1 JIS C8201-4-1 IEC 60947-4-1 EN 60947-1

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Product certifications	CSA CETLus CB CCC
Connections - terminals	Power circuit bar 2 Power circuit bolted connection Control circuit screw clamp terminals 1 0.00...0.01 in ² (1...4 mm ²)flexible without cable end Control circuit screw clamp terminals 2 0.00...0.01 in ² (1...4 mm ²)flexible with cable end Control circuit screw clamp terminals 1 0.00...0.01 in ² (1...4 mm ²)flexible with cable end Control circuit screw clamp terminals 2 0.00...0.00 in ² (1...2.5 mm ²)solid without cable end Control circuit screw clamp terminals 1 0.00...0.01 in ² (1...4 mm ²)
Tightening torque	Power circuit 513.34 lbf.in (58 N.m) Control circuit 10.62 lbf.in (1.2 N.m)
Mechanical durability	0.5 Mcycles
Inrush power in VA	1600...2400 VA, 40...400 Hz cos phi 0.9 (at 68 °F (20 °C))with LX1/LX9 coil 2000...2200 VA (at 68 °F (20 °C))with LX4 coil
Hold-in power consumption in VA	29...37 VA 8...10 VA
Maximum operating rate	600 cyc/h 131 °F (55 °C)

Environment

Protective treatment	TH
Ambient air temperature for operation	23...104 °F (-5...40 °C)
Ambient air temperature for storage	-76...176 °F (-60...80 °C)
Permissible ambient air temperature around the device	-40...140 °F (-40...60 °C)
Operating altitude	9842.52 ft (3000 m) without
Mechanical robustness	Vibrations contactor open2 Gn, 5...300 Hz Vibrations contactor closed4 Gn, 5...300 Hz Shocks contactor open6 Gn for 1/2 sine wave (11 ms) Shocks contactor closed15 Gn for 1/2 sine wave (11 ms)
Height	13.07 in (332 mm)
Width	17.24 in (438 mm)
Depth	9.39 in (238.6 mm)
Net weight	63.93 lb(US) (29 kg)

Ordering and shipping details

Category	22336 - CTR,F-LINE,AC,OPEN,NONREV
Discount Schedule	I12
GTIN	03606485242095
Package weight(Lbs)	26.58 kg (58.6 lb(US))
Returnability	No
Country of origin	CZ

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Contractual warranty

Warranty	18 months
----------	-----------
