

Product availability: Stock - Normally stocked in distribution facility



Main

Product	Combination Starter
Type	S
Control Circuit Type	Separate control circuit

Complementary

Control Circuit Voltage	110 V AC 50 Hz 120 V AC 60 Hz
Starter Type	Non reversing
Line Rated Current	27 A
Number of Poles	3P
Horsepower Rating	5 Hp 200 V AC, 3 phase 5 hp 230 V AC, 3 phase
Maximum Voltage Rating	600 V AC
Control Units	Selector switch HAND-OFF-AUTO)
Pilot Light	Red indicator on LED Green indicator off LED
Auxiliary Contacts	2 NO + 2 NC
Thermal overload type	Solid state Motor Logic class 10/20 3...9 A
Disconnect Type	Fusible disconnect switch H and K, 30 A, electrical SPDT
NEMA size	1
Height	609.60 mm (24 in)
Depth	211.84 mm (8.34 in)
Width	241.30 mm (9.5 in)
Handle Swing	82.55 mm (3.25 in)

Environment

Enclosure Type	NEMA 12 painted sheet steel with external reset
Product certifications	CSA UL listed

Ordering and shipping details

Category	21213 - 8538,39 SC,SD(NOT S*R,T,W)
Discount Schedule	CP1
GTIN	00785901169536
Package weight(Lbs)	17.90 kg (39.46 lb(US))
Returnability	Yes
Country of origin	MX

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds which is known to the State of California to cause Carcinogen & Reproductive harm. For more information go to www.p65warnings.ca.gov
EU RoHS Directive	Compliant EU RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------