8910DPA23V14

8910DPA definite purpose contactor, 25 A, 3P, 208/240 V 60 Hz 220 V 50 Hz coil, open

Product availability: Stock - Normally stocked in distribution facility



Main	
Product or component type	Definite Purpose Contactor
Line Rated Current	25 A
Number of Poles	3P
Pole contact composition	3 NO
Range of product	DPA

C			L
Com	nier	nen	ıarv
00111	PIOI		·u· y

Maximum Horse Power Rating	2 Hp 115 V AC, 1 phase	
waximum riorse r ower reating	5 Hp 230 V AC, 1 phase	
	10 Hp 230 V AC, 1 phase	
	15 Hp 460 V AC, 3 phase	
	20 hp 575 V AC, 3 phase	
Locked rotor rated current	125 A 460 V AC	
	100 A 575 V AC	
	150 A 277 V AC	
[Ue] rated operational voltage	600 V AC	
[Uc] control circuit voltage	24 V AC 50/60 Hz	
Phase	3 phase	
Electrical connection	Quick connect terminals	
	Binder head	

Environment

Product certifications UL recognized CSA	
------------------------------------------	--

Ordering and shipping details

Category	21342 - 8910 DPA 2_(25 AMP)
Discount Schedule	CP1B
GTIN	00785901080114
Package weight(Lbs)	0.49 kg (1.07 lb(US))
Returnability	Yes
Country of origin	CN

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals which are known to the State of California to cause Carcinogen & Reproductive harm. For more informa- tion go to www.p65warnings.ca.gov
REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant
Mercury free	Yes
RoHS exemption information	€Yes
China RoHS Regulation	China RoHS Declaration

Warranty 18 months

8910DPA23V14

Approximate Dimensions

