



Product availability: Stock - Normally stocked in distribution facility



Main

Product	Single Throw Safety Switch
Current Rating	400 A
Certifications	UL listed file E2875
Enclosure Rating	NEMA 3R/12 galvanized steel
Factory Installed Neutral	None
Disconnect Type	Fusible disconnect
Short Circuit Current Rating	10 KA H or K 200 kA R, J or L
Mounting Type	Surface
Number of Poles	3
Electrical Connection	Lugs
Duty Rating	Heavy duty
Voltage Rating	600 V AC/DC
Wire Size	AWG 1/0...750 kcmil copper or aluminium

Complementary

Width	666.75 mm (26.25 in)
Height	1174.75 mm (46.25 in)
Depth	257.30 mm (10.13 in)
Tightening torque	62.14 N.m (550 lbf.in) AWG 1/0...750 kcmil)

Ordering and shipping details

Category	00155 - H&HU SW,NEMA12,400-1200A
Discount Schedule	DE1
GTIN	00785901451815
Package weight(Lbs)	79.38 kg (175 lb(US))
Returnability	Yes
Country of origin	MX

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations

Contractual warranty

Warranty	18 months
----------	-----------