



Main

| | |
|---------------------------|------------------|
| Product or component type | Circuit breaker |
| Range of product | PowerPact H |
| Trip Unit Type | Thermal-magnetic |
| Breaking capacity code | D |

Complementary

| | |
|--------------------------------|---|
| Line Rated Current | 20 A |
| Number of Poles | 2P |
| Interrupt Rating | 25 KA 240 V AC 18 KA 480 V AC 14 KA 600 V AC 20 kA 250 V DC |
| [Ue] rated operational voltage | 250 V DC 600 V AC |
| Continuous current rating | 80 % |
| Mounting mode | I-Line |
| Electrical connection | I-Line connection line Lugs load |
| Wire Gauge | AWG 14...AWG 3/0 aluminium/copper |
| Phase | CA |
| Magnetic hold current | 350 A |
| Magnetic tripping current | 750 A |
| Height | 247.14 mm (9.73 in) |
| Width | 74.68 mm (2.94 in) |
| Depth | 121.92 mm (4.8 in) |
| Tightening torque | 44.25 lbf.in (5 N.m) 0.00...0.15 in ² (2.5...95 mm ²) AWG 14...AWG 3/0 |

Environment

| | |
|---------------------------------------|-------------------------------|
| Product certifications | CSA IEC UL listed CE |
| Ambient air temperature for operation | 104 °F (40 °C) |

Ordering and shipping details

| | |
|---------------------|------------------------------------|
| Category | 01112-HD, JD I-LINE BREAKER/SWITCH |
| Discount Schedule | DE2 |
| GTIN | 00785901750352 |
| Package weight(Lbs) | 3.00 lb(US) (1.361 kg) |
| Returnability | Yes |
| Country of origin | US |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS Declaration |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | No need of specific recycling operations |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|