

Product data sheet

Characteristics

VW3M5D2FR30

power cable 3m shielded 4x 1,3mm², BCH2
brake MIL connector

Product availability: Non-Stock - Not normally stocked in distribution facility



Main

Range of product	Lexium 28
Product or component type	Power cable
Accessory / separate part type	Preassembled power cordset
Accessory / separate part category	Connection accessory
Product compatibility	Servo motor BCH2 1000 W 3.94 in (100 mm)) with brake) Servo motor BCH2 2000 W 3.94 in (100 mm)) with brake) Servo motor BCH2 300 W 5.12 in (130 mm)) with brake) Servo motor BCH2 500 W 5.12 in (130 mm)) with brake) Servo motor BCH2 600 W 5.12 in (130 mm)) with brake) Servo motor BCH2 850 W 5.12 in (130 mm)) with brake) Servo motor BCH2 900 W 5.12 in (130 mm)) with brake) Servo motor BCH2 1000 W 5.12 in (130 mm)) with brake) Servo motor BCH2 1500 W 5.12 in (130 mm)) with brake) Servo motor BCH2 2000 W 5.12 in (130 mm)) with brake)
Accessory / separate part destination	Between servo motor and servo drive
Range compatibility	Lexium 28
Cable length	9.84 ft (3 m)

Complementary

Electrical connection	Free end servo drive side Connector - MIL small servo motor side
AWG gauge	6 x AWG 16
Net weight	1.43 lb(US) (0.65 kg)

Ordering and shipping details

Category	18263 - LEXIUM 32 ACCESSORIES
Discount Schedule	PC51
GTIN	03606480735714
Package weight(Lbs)	0.73 kg (1.6 lb(US))
Returnability	No
Country of origin	TN

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds which is known to the State of California to cause Carcinogen & Reproductive harm. For more information go to www.p65warnings.ca.gov
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.