



Product availability: Stock - Normally stocked in distribution facility



### Main

Product	Single Throw Safety Switch
Current Rating	30 A
Certifications	UL listed file E2875
Enclosure Rating	NEMA 3R/12 galvanized steel
Factory Installed Neutral	None
Disconnect Type	Non-fusible disconnect
Short Circuit Current Rating	200 kA maximum
Mounting Type	Surface
Number of Poles	3
Electrical Connection	Lugs
Duty Rating	Heavy duty
Voltage Rating	600 V AC/DC
Wire Size	AWG 12...AWG 6 aluminium AWG 14...AWG 6 copper

### Complementary

Width	191.77 mm (7.55 in)
Height	370.84 mm (14.6 in)
Depth	125.98 mm (4.96 in)
Tightening torque	5.08 N.M (45 lbf.in) 0.02 in <sup>2</sup> (13.3 mm <sup>2</sup> ) AWG 6) 4.52 N.M (40 lbf.in) 0.01 in <sup>2</sup> (8.367 mm <sup>2</sup> ) AWG 8) 3.95 N.m (35 lbf.in) 0.00...0.01 in <sup>2</sup> (2.06...5.261 mm <sup>2</sup> ) AWG 14...AWG 10)

### Ordering and shipping details

Category	00113 - H&HU SW,2&3P,N12,30-200A
Discount Schedule	DE1
GTIN	00785901505716
Package weight(Lbs)	4.51 kg (9.95 lb(US))
Returnability	Yes
Country of origin	US

### Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds which is known to the State of California to cause Carcinogen & Reproductive harm. For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	No need of specific recycling operations

## Contractual warranty

---

Warranty

18 months

---