# Product data sheet Characteristics

# ZCKD15

# limit switch head ZCKD - thermoplastic roller lever



Product availability: Stock - Normally stocked in distribution facility



Main	
Range of product	OsiSense XC
Series name	Standard format
Product or component type	Limit switch head
Device short name	ZCKD
Head type	Rotary head
Product compatibility	XCKL XCKM
Associated body	ZCKMD39 ZCKL1 ZCKLD31H7 ZCKLD35H7 ZCKMD35 ZCKM1H7 ZCKM5 ZCKM1H29 ZCKLD39H7 ZCKM8H29 ZCKLD39H7 ZCKM8H7 ZCKM8H7 ZCKLD37H7 ZCKLD37H7 ZCKL7 ZCKM6H29 ZCKLD37H7 ZCKM6H29 ZCKMD35H7 ZCKMB92 ZCKMD35H7 ZCKMB ZCKMD37H7 ZCKLD39 ZCKMD37H7 ZCKLD39 ZCKMD37 ZCKLB ZCKMD31 ZCKLD31 ZCKMD35H29 ZCKMD35H29 ZCKM6 ZCKLG ZCKLG ZCKLG ZCKMD31H7 ZCKMD31H7 ZCKMD31H7 ZCKMD31H7 ZCKMD39H7 ZCKMD39H7 ZCKMD39H7 ZCKMD37H29 ZCKLD35
Movement of operating	Rotary
head	Della la consecución a cada um discusso alla disc

Roller lever spring return thermoplastic

Lateral approach, 2 directions

ZCK D15 →

Type of operator

Type of approach

## Complementary

Switch actuation	By 30° cam
Positive opening	With
Head material	Metal

#### Environment

Ambient air temperature for operation	-13158 °F (-2570 °C)
Ambient air temperature for storage	-40158 °F (-4070 °C)
Environmental characteristic	Standard environment

### Ordering and shipping details

Category	22416 - LIMIT SWITCHES,IEC,XCKL	
Discount Schedule	Т	
GTIN	00785901646747	
Package weight(Lbs)	0.05 kg (0.1 lb(US))	
Returnability	Yes	
Country of origin	ID	

#### Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Di-isodecyl ph- thalate (DIDP) and Diisononyl phthalate (DINP) which is known to the State of California to cause Carcinogen and Reproductive harm. For more information go to www.p65warnings.ca.gov
REACh Regulation	REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EVEL RoHS Declaration
Mercury free	Yes
RoHS exemption information	₫ <sub>Yes</sub>
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations

#### Contractual warranty

Warranty	18 months
•	