



Product availability: Non-Stock - Not normally stocked in distribution facility



Main

Range	PowerLogic
Product name	PowerLogic ION7400
Device short name	ION7400
Product or component type	Power meter

Complementary

Power quality analysis	<ul style="list-style-type: none"> EN 50160 2010 compliance report IEEE 519 2014 compliance report IEC 61000-4-30 class S power quality measurement Up to the 63rd harmonic Harmonic distortion Waveform capture Voltage sag and swell detection Programmability (logic and math functions) IEC 62586 power quality monitoring IEC 61000-4-15 flicker Disturbance direction detection
Device application	<ul style="list-style-type: none"> Revenue billing WAGES metering Data aggregation Power monitoring
Type of measurement	<ul style="list-style-type: none"> Current Voltage Frequency Active and reactive power total Apparent power total Power factor total Active and reactive power per phase, rms Apparent power per phase, rms Power factor per phase, rms Active and reactive energy Apparent energy
Supply voltage	<ul style="list-style-type: none"> 90...415 V AC 45...65 Hz +/- 10 % 110...415 V DC +/- 10 %
Network frequency	<ul style="list-style-type: none"> 50 Hz 60 Hz
Line Rated Current	<ul style="list-style-type: none"> 10 A 5 A 1 A
Poles description	<ul style="list-style-type: none"> 1P + N 3P 3P + N
Power consumption in VA	18 VA 415 V AC
Display type	Colour TFT LCD
Display resolution	320 x 240 pixels QVGA
Sampling rate	256 samples/cycle
Measurement current	50...10000 mA

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Analogue input type	Voltage 5 MOhm) Current 0.3 MOhm)
Measurement voltage	57...400 V AC 42...69 Hz between phase and neutral 100...690 V AC 42...69 Hz between phases
Frequency measurement range	42...69 Hz
Number of inputs	3 digital 30 V AC 3 digital 60 V DC
Measurement accuracy	Current +/- 0.1 % Voltage +/- 0.1 % Active energy +/- 0.2 %
Accuracy class	Class 0.2S active energy IEC 62053-22 Class 0.2 active energy ANSI C12.20 Class 0.2 active power IEC 61557-12 Class 0.5S reactive energy IEC 62053-24 Class 0.5 power factor IEC 61557-12 Class 0.2 voltage IEC 61557-12 Class 0.2 current IEC 61557-12 Class 0.2 frequency IEC 61557-12 Class 0.2 active energy IEC 61557-12
Number of outputs	1 pulse
Information displayed	Voltage Current Frequency Power Energy consumption Harmonic distortion
Communication port protocol	Modbus RTU 115 kbauds - 2-wire ION 115 kbauds - 2-wire DNP3 IEC 61850 Modbus TCP/IP Ethernet Modbus TCP/IP daisy chain 10/100 Mbit/s RSTP 801.1d 2004 Ansi C12.19 DLMS
Communication port support	Ethernet Screw terminal block RS485 Optical probe fiber optic Mini B USB USB
Communication network type	IPv6 (internet protocol)
Data recording	Alarm logs Waveform logs Sequence of event recording Event logs Sag and swell logs Data logs Harmonics logs GPS synchronisation Time stamping Trending/Forecasting Min/max of instantaneous values
Memory capacity	512 MB
Web services	Customizable home page File upload/download via FTP File upload/download via SFTP Web server Alarm notification by e-mail Viewing of captured waveform (FTP) Viewing of captured waveform (web) HTTPS server
Communication service	DHCP RSTP support NTP time synchronization SMTP e-mail notification PTP time synchronization
Cybersecurity	Syslog protocol support Robust security logs Enable/Disable communication ports Password protection Port hardening
Mounting mode	Flush-mounted
Mounting support	Framework

Type of installation	Indoor installation
Installation category	III
Safety Construction	III, 400...690 V IEC 61010-1:ed. 3 III, 400...690 V EN 61010-1:ed. 3 III, 347...600 V UL 61010-1:ed. 3 III, 347...600 V CSA C22.2 No 61010-1:ed. 3
Standards	IEC 62053-22 IEC 62052-11 IEC 62053-24 IEC 61557-12 IEC 61326-1 IEEE 1588 IEC 62586
Product certifications	CE CULus N998 China RoHS
Width	3.86 in (98 mm)
Depth	3.09 in (78.5 mm)
Height	4.41 in (112 mm)
Product weight	24.90 oz (706 g)

Environment

Electromagnetic compatibility	Electrostatic discharge IEC 61000-4-2 Radiated radio-frequency electromagnetic field immunity test IEC 61000-4-3 Electrical fast transient/burst immunity test IEC 61000-4-4 Surge immunity test IEC 61000-4-5 Conducted RF disturbances IEC 61000-4-6 Magnetic field at power frequency IEC 61000-4-8 Voltage dips and interruptions immunity test IEC 61000-4-11 Immunity to impulse waves IEC 61000-4-12 Conducted and radiated emissions EN 55022 Conducted and radiated emissions EN 55011 Conducted and radiated emissions FCC Part 15 Conducted and radiated emissions ICES-003 Conducted RF disturbances 2...150 Hz) CLC/TR 50579 Surge withstand IEEE C37.90.1
IP degree of protection	Front IP54 IEC 60529 Body IP30 IEC 60529
Relative humidity	5...95 %
Ambient air temperature for operation	-13...158 °F (-25...70 °C)
Ambient air temperature for storage	-40...185 °F (-40...85 °C)
Operating altitude	9842.52 ft (3000 m)

Ordering and shipping details

Category	09753 - POWERLOGIC ION 7400 HARDWARE
Discount Schedule	PM1
GTIN	00785901643173
Package weight(Lbs)	3.63 kg (8 lb(US))
Returnability	No

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Dichloromethane (Methylene chloride) and Bisphenol A (BPA) which is known to the State of California to cause Carcinogen and Reproductive harm. For more information go to www.p65warnings.ca.gov
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	 Yes

China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
