Product data sheet Characteristics

9001KM31LY PILOT LIGHT MODULE 6V 30MM T-K+SK+KX



Product availability: Non-Stock - Not normally stocked in distribution facility



Harmony 9001SK Harmony 9001K
Light block
9001K
BA 9s
Direct via integral resistance

Complementary

Net weight	0.11 lb(US) (0.05 kg)
Light source	Incandescent
[Us] rated supply voltage	12 V AC/DC

Environment

LITTION		
Protective treatment	TC	
Ambient air temperature for storage	-40158 °F (-4070 °C)	
Ambient air temperature for operation	-13158 °F (-2570 °C)	
IP degree of protection	IP20 IEC 60529	
Standards	EN/IEC 60947-5-1 CSA C22.2 No 14 EN/IEC 60947-1 EN/IEC 60947-5-4 UL 508 JIS C 4520 JIS C 852	
Product certifications	NEMA UL 508	
Electrical shock protection class	Class II IEC 61140	
Vibration resistance	7 gn 2500 Hz)IEC 60068-2-6	
Shock resistance	50 gn IEC 60068-2-27	

Ordering and shipping details

Category	21435 - 9001 KM LIGHT MODULES
Discount Schedule	CS1
Package weight(Lbs)	0.11 kg (0.25 lb(US))
Returnability	No
Country of origin	MX

Offer Sustainability

Warranty

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds which is known to the State of California to cause Carcinogen & Reproductive harm. For more information go to www.p65warnings.ca.gov
REACh Regulation	REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	☑ China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations Find of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

18 months