



Main

Product or component type	Automatic switch
Range of product	PowerPact L
Trip unit technology	Magnetic

Complementary

Line Rated Current	400 A
[Ue] rated operational voltage	600 V AC
Mounting mode	I-Line
Poles description	3P
Breaking capacity	125 KA 240 V AC 100 KA 480 V AC 50 kA 600 V AC
Breaking capacity code	L
Electrical connection	Lugs load I-Line connection line
AWG gauge	AWG 3/0...500 kcmil aluminium/copper)2
Terminal identifier	AL600LF52K3
Magnetic tripping current	4800 A
Height	339.85 mm (13.38 in)
Width	139.95 mm (5.51 in)
Depth	167.89 mm (6.61 in)
Tightening torque	442.54 lbf.in (50 N.m) 0.15...0.37 in ² (95...240 mm ²) AWG 3/0...500 kcmil)

Environment

Product certifications	CE NMX CSA UL listed CCC IEC
------------------------	---

Ordering and shipping details

Category	01118-L ELEC TRIP I-LINE BREAKER/SW
Discount Schedule	DE2
GTIN	00785901133391
Package weight(Lbs)	17.00 lb(US) (7.711 kg)
Returnability	Yes
Country of origin	US

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: DIDP and DINP which is known to the State of California to cause Carcinogen and Reproductive harm. For more information go to www.p65warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information

Contractual warranty

Warranty	18 months
----------	-----------