Product availability: Stock - Normally stocked in distribution facility



Main Range of product Harmony XAC Product or component Head for push-button Component name XACB Unmarked Marking Operator additional in-Booted formation Operating travel 0.16 in (4 mm) Cap/operator or lens Red colour Product compatibility XENB.... XESD2251 XESD2241 XESD2201 XEND... XESB2011 XENC.... Sale per indivisible 10

Complementary

	·
Net weight	0.01 lb(US) (0.005 kg)

quantity

Environment

Environment				
Standards	CSA C22.2 No 14 IEC 60947-5-1			
	EN 60947-5-1			
Ambient air temperature for operation	-13158 °F (-2570 °C)			
Ambient air temperature for storage	-40158 °F (-4070 °C)			
Vibration resistance	15 gn 10500 Hz)IEC 60068-2-6			
Shock resistance	100 gn IEC 60068-2-27			
Electrical shock protection class	Class II IEC 61140			
IP degree of protection	IP65 IEC 60529			
IK degree of protection	IK08 EN 50102			

Ordering and shipping details

22473 - PUSHBUTTON, PENDANTS	
CS2	
00785901640868	
0.00 kg (0.01 lb(US))	
Yes	
CZ	
	CS2 00785901640868 0.00 kg (0.01 lb(US)) Yes

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds and Di-isodecyl phthalate (DIDP) which is known to the State of California to cause Carcinogen and Reproductive harm. For more information go to www.p65warnings.ca.gov		
REACh Regulation	REACh Declaration		
REACh free of SVHC	Yes		
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EVEU RoHS Declaration		
Toxic heavy metal free	Yes		
Mercury free	Yes		
RoHS exemption information	₫Yes		
China RoHS Regulation	☐ China RoHS Declaration		

Contractual warranty

\	40	
Warranty	18 months	