Product data sheet
Characteristics

GV2MP04
TeSys GV2 - Reduced flush mounting enclosure for TeSys GV2ME - IP55

Green Premium

Product availability: Stock - Normally stocked in distribution facility

Main

Range	TeSys
Product or component type	Enclosure
Device short name	GV2MP
Accessory / separate part category	Mounting accessory
Product compatibility	GV2ME
Enclosure type	Reduced flush mounting

Complementary

Auxiliary mounting location	Right
Height	5.24 in (133 mm)
Width	3.66 in (93 mm)
Depth	3.86 in (98 mm)
Product weight	0.29 lb(US) (0.13 kg)

Environment

IP degree of protection	IP55 front face
Environmental characteristic	Standard environment

Ordering and shipping details

Category	22367 - MANUAL STR PROTECTOR - GV2
Discount Schedule	I11
GTIN	00785901545866
Package weight(Lbs)	0.21 kg (0.47 lb(US))
Returnability	Yes
Country of origin	CZ

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Contractual warranty

Warranty	18 months