



Product availability: Stock - Normally stocked in distribution facility



Main

| | |
|---------------------------|-------------------------|
| Product or component type | Motor Circuit Protector |
| Range of product | PowerPact H |
| Trip Unit Type | Electronic |
| Breaking capacity code | J |

Complementary

| | |
|---|---|
| Line Rated Current | 30 A |
| Number of Poles | 3P |
| Interrupt Rating | 100 KA 240 V AC 65 KA 480 V AC 25 KA 600 V AC 20 kA 250 V DC |
| [Ue] rated operational voltage | 600 V AC |
| Continuous current rating | 80 % |
| Mounting mode | Unit mount |
| Electrical connection | Lugs load Lugs line |
| Wire Gauge | AWG 14...AWG 3/0 aluminium/copper |
| [Ith] conventional free air thermal current | 1.5...25 A |
| Magnetic tripping current | 9...325 A |
| Height | 162.56 mm (6.4 in) |
| Width | 104.65 mm (4.12 in) |
| Depth | 110.74 mm (4.36 in) |
| Tightening torque | 44.25 lbf.in (5 N.m) 0.00...0.15 in ² (2.5...95 mm ²) AWG 14...AWG 3/0 |

Environment

| | |
|---------------------------------------|------------------------|
| Product certifications | CE CCC IEC UR |
| Ambient air temperature for operation | 104 °F (40 °C) |

Ordering and shipping details

| | |
|---------------------|---|
| Category | 01125 - HJ, JJ UNT MNT MTR CIRCUIT PROTECTR |
| Discount Schedule | DE2 |
| GTIN | 00785901492948 |
| Package weight(Lbs) | 1.99 kg (4.38 lb(US)) |
| Returnability | Yes |
| Country of origin | MX |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS Declaration |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | No need of specific recycling operations |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

Approximate Dimensions

