

Product availability: Non-Stock - Not normally stocked in distribution facility



Main

Range of product	Preventa Safety automation
Product or component type	Preventa safety module
Safety module name	XPSBAE
Safety module application	For electrical monitoring of two-hand control stations
Function of module	Monitoring two-hand control station type IIIA
Safety level	Can reach PL c/category 1 EN/ISO 13849-1 Can reach SILCL 1 EN/IEC 62061
Safety reliability data	MTTFd = 55 years EN/ISO 13849-1 PFHd = 2.1E-6 1/h EN/IEC 62061
Connections - terminals	Captive screw clamp terminals, 1 x 0.25...1 x 1.5 mm ² flexible with cable end, with bezel Captive screw clamp terminals, 1 x 0.25...1 x 2.5 mm ² flexible with cable end, without bezel Captive screw clamp terminals, 2 x 0.25...2 x 1 mm ² flexible with cable end, without bezel Captive screw clamp terminals, 2 x 0.5...2 x 1.5 mm ² flexible with cable end, with double bezel Captive screw clamp terminals, 1 x 0.2...1 x 2.5 mm ² stranded without cable end Captive screw clamp terminals, 1 x 0.2...1 x 2.5 mm ² solid without cable end Captive screw clamp terminals, 2 x 0.2...2 x 1.5 mm ² stranded without cable end Captive screw clamp terminals, 2 x 0.2...2 x 1 mm ² solid without cable end
Output type	Relay, 1 NO, volt-free
Number of additional circuits	1 NC
[Us] rated supply voltage	115...230 V AC - 15...10 %

Complementary

Synchronisation time between inputs	0.5 s
Supply frequency	50/60 Hz
Maximum power consumption in VA	3.3 VA
Input protection type	Internal, electronic
Number of inputs	1 NC + NO
Input current	2.5 mA NC 25 mA NO
Input compatibility	Two-hand control EN 574
[Uc] control circuit voltage	24 V DC
Breaking capacity	180 VA holding AC-15 C300 relay output 1800 VA inrush
Breaking capacity	3 A 24 V DC-13)20 ms relay output
[Ith] conventional free air thermal current	5 A
Associated fuse rating	4 A gG relay output EN/IEC 60947-5-1 6 A fast blow
Minimum output current	10 mA relay output
Minimum output voltage	17 V relay output
Maximum response time on input open	20 ms
[Ui] rated insulation voltage	300 V 2)IEC 60947-5-1

[Uimp] rated impulse withstand voltage	4 KV III IEC 60947-5-1 4 kV III DIN VDE 0110 part 1
Local signalling	2 LEDs
Mounting support	35 mm symmetrical DIN rail
Product weight	0.22 lb(US) (0.1 kg)

Environment

Standards	EN 574 type III A EN 62061 EN/IEC 60947-5-1 EN 60947-01 EN/ISO 13849-1 EN/IEC 60204-1
Product certifications	CSA UL TÜV
IP degree of protection	IP20 terminals)EN/IEC 60529 IP40 enclosure)EN/IEC 60529
Ambient air temperature for operation	-13...131 °F (-25...55 °C)
Ambient air temperature for storage	-13...167 °F (-25...75 °C)

Ordering and shipping details

Category	22477 - SAFETY MODULES (PREVENTA)
Discount Schedule	SAF2
GTIN	00785901958239
Package weight(Lbs)	0.10 kg (0.22 lb(US))
Returnability	No
Country of origin	DE

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds which is known to the State of California to cause Carcinogen & Reproductive harm. For more information go to www.p65warnings.ca.gov
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Contractual warranty

Warranty	18 months
----------	-----------

Dimensions

