

# LAL364001253

## FA/LA MOLDED CASE CIRCUIT BREAKER 600V, 400A, 3P, AUX SWITCH, BELL ALARM

Product availability: Non-Stock - Not normally stocked in distribution facility



### Main

Product or component type	Circuit breaker
Trip Unit Type	Thermal-magnetic
Options	Auxiliary switch 1 NO + 1 NC Alarm switch

### Complementary

Line Rated Current	400 A
Number of Poles	3P
Interrupt Rating	42 KA 240 V AC 30 KA 480 V AC 22 KA 600 V AC 10 KA 125 V DC 10 kA 250 V DC
[Ue] rated operational voltage	600 V AC 250 V DC
Mounting mode	Unit mount
Electrical connection	Lugs load Lugs line
Wire Gauge	AWG 1...600 kcmil aluminium/copper)1 AWG 1...250 kcmil aluminium/copper)2
Terminal Type	AL400LA
Magnetic hold current	2000 A
Magnetic tripping current	4000 A
Height	279.40 mm (11 in)
Width	152.40 mm (6 in)
Depth	148.34 mm (5.84 in)
Tightening torque	115.06 Lbf.in (13 N.m) 0.07...0.47 in <sup>2</sup> (42...304 mm <sup>2</sup> ) AWG 1...600 kcmil) 115.06 lbf.in (13 N.m) 0.07...0.20 in <sup>2</sup> (42...127 mm <sup>2</sup> ) AWG 1...250 kcmil)

### Environment

Product certifications	CSA UL listed IEC
------------------------	-------------------------

### Ordering and shipping details

Category	00935 - LAL/LHL BRKR, SW, MAG-GARD
Discount Schedule	DE2
GTIN	00785901613923
Package weight(Lbs)	6.80 kg (15 lb(US))
Returnability	No
Country of origin	MX

## Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: DIDP and DINP which is known to the State of California to cause Carcinogen and Reproductive harm. For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>

## Contractual warranty

Warranty	18 months
----------	-----------