

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

| | |
|---------------------|----------------------------|
| Product | Duplex Unit Manual Starter |
| Type | F |
| Overload Relay Type | Melting alloy |

Complementary

| | |
|-----------------------|---|
| Current Rating | 16 A |
| Cable entry | Without |
| Horsepower Rating | 1 Hp 115 V AC 1 Hp 230 V AC 1 hp 277 V AC |
| Voltage Rating | 277 V AC |
| Number of Poles | 1P |
| Control Unit | Toggle switch |
| Number of Phases | 1 phase |
| Pilot Light | Red indicator |
| Reset | Manual |
| Motor starter type | 2 speed |
| Electrical connection | Screw clamp terminals |
| Wire Gauge | AWG 14...AWG 12 copper |
| Height | 133.35 mm (5.25 in) |
| Width | 133.35 mm (5.25 in) |
| Depth | 92.20 mm (3.63 in) |

Environment

| | |
|------------------------|---|
| Product certifications | UL listed file E42243 CCN NLRV CE CSA LR25490 class 3211 05 |
| NEMA Enclosure Rating | Not rated (flush plate) stainless steel standard size |

Ordering and shipping details

| | |
|---------------------|--------------------------|
| Category | 21101 - 2510,2511,2512 F |
| Discount Schedule | CP1 |
| GTIN | 00785901554837 |
| Package weight(Lbs) | 0.60 kg (1.33 lb(US)) |
| Returnability | No |
| Country of origin | MX |

Offer Sustainability

| | |
|---------------------------|---|
| California proposition 65 | WARNING: This product can expose you to chemicals including: Lead and lead compounds which is known to the State of California to cause Carcinogen & Reproductive harm. For more information go to www.p65warnings.ca.gov |
| REACH Regulation | REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Not compliant |
| China RoHS Regulation | China RoHS Declaration |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|