

Product availability: Non-Stock - Not normally stocked in distribution facility



### Main

Product or component type	Controllers separate parts
Accessory / separate part category	Control accessories
Product specific application	Medium hoisting applications Heavy hoisting applications Light hoisting applications
Product compatibility	XKB XKD XKM
Accessory / separate part type	Potentiometer
Condition of use	For standard applications
Ohmic value	10000 Ohm
Size	15 mm

### Complementary

Standards	UTE 93-265
Potentiometer characteristic	Linear function Continuous rotational operation
Operating angle	360 °
Mechanical durability	3000000 cycles
Centre tap	Wired out to terminal
Centre tap dead zone	2 ° +/- 1 %
Power dissipation in W	3 W 185 °F (85 °C)
Connections - terminals	Flying leads from soldered standard tags
Net weight	0.13 lb(US) (0.06 kg)

### Environment

Mounting mode	By the body
---------------	-------------

### Ordering and shipping details

Category	22474 - PUSHBUTTON,CRANE JOYSTICKS
Discount Schedule	I
GTIN	00785901850038
Package weight(Lbs)	0.06 kg (0.14 lb(US))
Returnability	No
Country of origin	FR

### Offer Sustainability

REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

## Contractual warranty

---

Warranty

18 months

---