



Main

| | |
|---------------------------|------------------|
| Product or component type | Circuit breaker |
| Range of product | PowerPact Q |
| Trip unit technology | Thermal-magnetic |

Complementary

| | |
|--------------------------------|--|
| Line Rated Current | 125 A |
| [Ue] rated operational voltage | 240 V AC |
| Number of poles | 2 |
| Breaking capacity | 100 kA 240 V AC |
| Continuous current rating | 80 % |
| Breaking capacity code | J |
| Mounting mode | Unit mount |
| Electrical connection | Lugs load AWG 4...300 kcmil aluminium/copper Lugs line AWG 4...300 kcmil aluminium/copper |
| Magnetic hold current | 1200 A |
| Magnetic tripping current | 2400 A |
| Height | 164.34 mm (6.47 in) |
| Width | 114.30 mm (4.5 in) |
| Depth | 99.82 mm (3.93 in) |
| Tightening torque | 247.82 lbf.in (28 N.m) 0.04...0.23 in ² (25...150 mm ²) AWG 4...300 kcmil |

Environment

| | |
|------------------------|-------------------------|
| Product certifications | IEC CSA UL listed |
|------------------------|-------------------------|

Ordering and shipping details

| | |
|---------------------|---------------------------------|
| Category | 00005-QO,Q2L 2P ENCL & BREAKERS |
| Discount Schedule | DE2A |
| GTIN | 00785901705581 |
| Package weight(Lbs) | 3.35 lb(US) (1.520 kg) |
| Returnability | Yes |
| Country of origin | MX |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| California proposition 65 | WARNING: This product can expose you to chemicals including: DIDP and DINP which is known to the State of California to cause Carcinogen and Reproductive harm. For more information go to www.p65warnings.ca.gov |
| REACH Regulation | REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS Declaration |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | No need of specific recycling operations |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|