

Product data sheet

Characteristics

VW3M5D1AR30

power cable 3m shielded 4x 0,82mm², BCH2 leads connection

Product availability: Stock - Normally stocked in distribution facility



Main

Range of product	Lexium 28
Product or component type	Power cable
Accessory / separate part type	Preassembled power cordset
Accessory / separate part category	Connection accessory
Product compatibility	Servo motor BCH2 50 W 1.57 in (40 mm) without brake) Servo motor BCH2 100 W 1.57 in (40 mm) without brake) Servo motor BCH2 200 W 2.36 in (60 mm) without brake) Servo motor BCH2 400 W 2.36 in (60 mm) without brake) Servo motor BCH2 400 W 3.15 in (80 mm) without brake) Servo motor BCH2 750 W 3.15 in (80 mm) without brake)
Accessory / separate part destination	Between servo motor and servo drive
Range compatibility	Lexium 28
Cable length	9.84 ft (3 m)

Complementary

Electrical connection	Free end servo drive side Connector - Molex 4-pin servo motor side
AWG gauge	4 x AWG 18
Net weight	0.66 lb(US) (0.3 kg)

Ordering and shipping details

Category	18264 - LEXIUM 23/28 ACCESSORIES
Discount Schedule	PC51
GTIN	00785901981381
Package weight(Lbs)	0.44 kg (0.96 lb(US))
Returnability	Yes
Country of origin	TN

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds which is known to the State of California to cause Carcinogen & Reproductive harm. For more information go to www.p65warnings.ca.gov
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration