

Product data sheet

Characteristics

2510KG1

Manual switch, 2 P, 30 amp, toggle operated, no pilot light, 600 VAC, NEMA 1 enclosure

Product availability: Stock - Normally stocked in distribution facility



Main

| | |
|---------|---------------------------|
| Product | Single Unit Manual Switch |
| Type | K |

Complementary

| | |
|------------------------|--|
| Current Rating | 30 A |
| Cable Entry | 0.5" and 0.75" knock-outs (top and bottom) |
| Horsepower Rating | 2 Hp 115 V AC 2 Hp 230 V AC 3 Hp 460 V AC 3 Hp 575 V AC 1 Hp 90 V DC 2 Hp 115 V DC 1.5 hp 230 V DC |
| Maximum Voltage Rating | 600 V AC 230 V DC |
| Number of Poles | 2P |
| Control Unit Type | Toggle |
| Number of Phases | 1 phase |
| Pilot Light | No indicator |
| Starter Type | Non reversing |
| Electrical Connection | Screw clamp terminals |
| Wire Gauge | AWG 14...AWG 10 copper |
| Height | 107.95 mm (4.25 in) |
| Width | 61.98 mm (2.44 in) |
| Depth | 69.85 mm (2.75 in) |
| Net weight | 0.84 lb(US) (0.38 kg) |

Environment

| | |
|-----------------------|---|
| Certifications | UL listed file E42243 CCN NLRV CSA LR25490 class 3211 05 |
| NEMA Enclosure Rating | NEMA 1 plastic standard size |

Ordering and shipping details

| | |
|---------------------|--------------------------|
| Category | 21102 - 2510,2511,2512 K |
| Discount Schedule | CP1 |
| GTIN | 00785901554479 |
| Package weight(Lbs) | 0.36 kg (0.8 lb(US)) |
| Returnability | Yes |
| Country of origin | MX |

Offer Sustainability

| | |
|---------------------------|---|
| California proposition 65 | WARNING: This product can expose you to chemicals including: Lead and lead compounds which is known to the State of California to cause Carcinogen & Reproductive harm. For more information go to www.p65warnings.ca.gov |
| REACH Regulation | REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Not compliant |
| China RoHS Regulation | China RoHS Declaration |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|