

Product availability: Stock - Normally stocked in distribution facility



### Main

Range	Linergy
Product name	HK
Product or component type	Plug outlet
Poles description	3P
[Ith] conventional free air thermal current	32 A
I <sup>2</sup> t on activation	200000 A <sup>2</sup> .s
Number of points	2
Number of cables	3 0.01 in <sup>2</sup> (4 mm <sup>2</sup> )
Cable length	0.82 ft (0.25 m)
Quantity per set	Set of 6

### Complementary

[Ui] rated insulation voltage	600 V CSA 600 V UL 690 V IEC 60439-1
Peak current	25 kA
Width	0.71 in (18 mm)
Height	1.79 in (45.5 mm)
Depth	1.50 in (38 mm)
Net weight	0.10 lb(US) (0.045 kg)





### Environment

Standards	IEC 60439
Product certifications	DNV LROS (Lloyds register of shipping) CSA UL

### Ordering and shipping details

Category	22623 - PANEL BUS (AK5)
Discount Schedule	I11
GTIN	00785901576853
Package weight(Lbs)	0.06 kg (0.13 lb(US))
Returnability	Yes
Country of origin	FR

### Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 <a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant  <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	 <a href="#">Yes</a>
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>

Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	No need of specific recycling operations
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

### Contractual warranty

Warranty	18 months
----------	-----------