

Product data sheet

Characteristics

8536SBO2V02S

Nonreversing magnetic starter, Size 0, 18 A, 3P, 110/120 VAC 50/60 Hz coil, melting alloy overload, open style

Product availability: Stock - Normally stocked in distribution facility



Main

Product or component type	Starter
Type	S
Control Circuit Type	Separate control circuit

Complementary

Control Circuit Voltage	110 V AC 50 Hz 120 V AC 60 Hz
Motor starter type	Non reversing
Current Rating	18 A
Number of Poles	3P
Number of Phases	3 phase
Horsepower Rating	3 HP 200 V AC 3 HP 230 V AC 5 HP 460 V AC 5 HP 575 V AC
Maximum Voltage Rating	600 V AC
Control Units	No control units
Thermal overload type	Melting alloy 3
Electrical connection	Screw clamp terminals
NEMA size	0
Height	6.77 in (172 mm)
Depth	4.21 in (107 mm)
Width	3.50 in (89 mm)
Net weight	3.99 lb(US) (1.81 kg)

Environment

Enclosure Type	Not rated (open device)
Product certifications	CSA UL listed NEMA

Ordering and shipping details

Category	21191 - 8502,36 SA,SB(NOT S*R,T,W)
Discount Schedule	CP1
GTIN	00785901864639
Package weight(Lbs)	1.81 kg (4 lb(US))
Returnability	Yes
Country of origin	MX

Offer Sustainability

EU RoHS Directive	Not compliant
China RoHS Regulation	China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------