

Product availability: Stock - Normally stocked in distribution facility



Main

Range	TeSys
Device short name	LUL
Product or component type	Communication module
Product compatibility	LUCA LUCL LUCD LUCC LUCM LUCB
Device application	Communication
Range compatibility	TeSys U LUB non reversing power base TeSys U LU2B reversing power base

Complementary

Main function available	Communication module
Mounting mode	Plug-in
Mounting location	Front side
Physical interface	9-way SUB-D female
Bus type	CANopen
Communication port protocol	CAN2.0A CAN2.B
Addressing	1...127
Current consumption	1.5 mA 24 V DC 20...28 V
Logic input	Positive 24 V DC - 7 mA
Response time	10 ms +/- 30 % change to state 0 10 ms +/- 30 % change to state 1
Input type	Resistive
Number of outputs	2 dedicated to starter-controller coil operation 1
[Us] rated supply voltage	24 V DC
Output current	<= 500 mA
Protection type	GL fuse 2 A
Switching current capacity	0.5 mA 24 V
Local signalling	3 LEDs front panel
Connection pitch	0.15 in (3.81 mm)
Connections - terminals	Screw clamp terminals 1 0.00...0.00 in ² (0.14...1 mm ²)flexible without cable end Screw clamp terminals 1 0.00...0.00 in ² (0.14...1 mm ²)rigid without cable end Screw clamp terminals 1 0.00...0.00 in ² (0.25...0.5 mm ²)flexible with cable end Screw clamp terminals 1 0.00...0.00 in ² (0.25...1 mm ²)flexible with cable end Screw clamp terminals 2 0.00...0.00 in ² (0.14...0.5 mm ²)rigid without cable end Screw clamp terminals 2 0.00...0.00 in ² (0.14...0.75 mm ²)flexible without cable end Screw clamp terminals 2 0.00...0.00 in ² (0.25...0.34 mm ²)flexible with cable end Screw clamp terminals 2 0.00 in ² (0.5 mm ²)flexible with cable end
Associated cable type	AWG 26...AWG 16
Tightening torque	1.77...2.21 lbf.in (0.2...0.25 N.m) 0.10 in (2.5 mm)

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environment

Standards	DR 303-2 CIADS-301 V4.02
Ambient air temperature for operation	-13...131 °F (-25...55 °C)
IP degree of protection	IP20 IEC 60529

Ordering and shipping details

Category	22398 - TESYS U - MULTI-FCTN CTRL MOD(LUCM)
Discount Schedule	I11
GTIN	00785901841456
Package weight(Lbs)	0.10 kg (0.23 lb(US))
Returnability	Yes
Country of origin	FR

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Contractual warranty

Warranty	18 months
----------	-----------