Product data sheet Characteristics

9001SKT35 PILOT LIGHT 28V 30MM SK +OPTIONS



Product availability: Stock - Normally stocked in distribution facility

Main



Full voltage 24 V Full voltage 28 V



Complementary

Bezel material	Plastic
Mounting diameter	1.18 in (30 mm)
Shape of signaling unit head	Round
Operating mode	Push-to-test

Environment

Protective treatment	TC
IP degree of protection	IP66

Ordering and shipping details

Category	21429 - 9001 SK,SKY	
Discount Schedule	CS1	
GTIN	00785901959939	
Package weight(Lbs)	0.12 kg (0.26 lb(US))	
Returnability	Yes	
Country of origin	MX	

Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	☑REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EVEU RoHS Declaration	
Toxic heavy metal free	Yes	
Mercury free	Yes	
RoHS exemption information	₫Yes	
China RoHS Regulation	☑ China RoHS Declaration	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	No need of specific recycling operations Find of Life Information	
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.	

Warranty 18 months