



### Main

Product or component type	Automatic switch
Range of product	PowerPact L
Trip unit technology	Magnetic

### Complementary

Line Rated Current	400 A
[Ue] rated operational voltage	600 V AC
Mounting mode	I-Line
Poles description	3P
Breaking capacity	65 KA 240 V AC 35 KA 480 V AC 18 kA 600 V AC
Breaking capacity code	G
Electrical connection	Lugs load I-Line connection line
AWG gauge	AWG 3/0...500 kcmil aluminium/copper)2
Terminal identifier	AL600LF52K3
Magnetic tripping current	4800 A
Height	339.85 mm (13.38 in)
Width	139.95 mm (5.51 in)
Depth	167.89 mm (6.61 in)
Tightening torque	442.54 lbf.in (50 N.m) 0.15...0.37 in <sup>2</sup> (95...240 mm <sup>2</sup> ) AWG 3/0...500 kcmil)

### Environment

Product certifications	UL listed CE IEC CSA CCC NMX
------------------------	---

### Ordering and shipping details

Category	01118-L ELEC TRIP I-LINE BREAKER/SW
Discount Schedule	DE2
Package weight(Lbs)	17.00 lb(US) (7.711 kg)
Returnability	Yes
Country of origin	US

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: DIDP and DINP which is known to the State of California to cause Carcinogen and Reproductive harm. For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>

## Contractual warranty

Warranty	18 months
----------	-----------