

# 9070EL2D9

## INDUSTRIAL CONTROL TRANSFORMER

### 100VA MULTI-VOLTAGE WITH

### 610mm/24INCH LEADS



Product availability: Stock - Normally stocked in distribution facility



#### Main

Product or component type	Industrial Control Transformer
Range of product	EL

#### Complementary

Phase	1 phase
Rated power in VA	100 VA
Primary voltage	480 V 460 V 440 V
Secondary voltage	110 V 115 V 120 V
Temperature rise	55 °C
Electrical connection	Screw clamp terminals
Connector type	Lead 2001.31 ft (610 m)

#### Environment

Product certifications	CSA UL listed CE
NEMA degree of protection	Not rated (open device)
Insulation temperature	221 °F (105 °C)

#### Ordering and shipping details

Category	21691 - 9070 AP,E,G,H,SB
Discount Schedule	CP8
GTIN	00785901020226
Package weight(Lbs)	1.84 kg (4.05 lb(US))
Returnability	Yes
Country of origin	MX

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Phenyl glycidyl ether which is known to the State of California to cause Carcinogen & Reproductive harm. For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	No need of specific recycling operations

## Contractual warranty

Warranty	18 months
----------	-----------