



	SPECIFICATIONS			
	CONTACT CARRIER MATERIAL/COLOR	NYLON OR TPU/YELLOW		
CONTACT MATERIAL/PLATING		BRASS/GOLD		
	RATED CURRENT [A]	4.0 A		
1	RATED VOLTAGE [V]	250 V		
HOUSING MATERIAL		BRASS/NICKEL		
	CONDUCTOR INSULATION MATERIAL	PVC		
NUMBER OF CONDUCTORS [AWG]		4×22 AWG		
	TEMPERATURE RATING	-40°C to +105°C (-40°F to +221°F)		
	PROTECTION CLASS	MEETS NEMA 1,3,4,6P AND IEC IP68		





CABLE LENGTH	TOLERANCE *			
ALL LENGTHS	+ 4% (OR 50mm) OF LENGTH - 0% (OR 0mm) OF LENGTH WHICHEVER IS GREATER			
STRIP LENGTH	TOLERANCE *			
0-7mm	±0.5mm			
8-29mm	±1.0mm			
30-49mm	±2.0mm			
50-69mm	±3.0mm			
70-100mm	±4.0mm			
OVER 100mm	±5.0mm			
* UNLESS OTHERWISE SPECIFIED				

NOTES:

1. "*" INDICATES LEAD LENGTH IN METERS. CONTACT TURCK TO ORDER SPECIFIC LENGTHS.

С	DRAWING PROCESSED AS PART OF ECO 33971	СВМ	04/06/11	33971
REV	DESCRIPTION	BY	DATE	ECO NO.

SOURCE DRAWING - FOR REFERENCE ONLY

RELATED DOCUMENTS 1. 2. 3. 4.	3RD ANGLE PROJECTION	THIS DRAWING IS CONFIDENTIAL AND THE PROPERTY OF TURCK INC. USE OF THIS DOCUMENT WITHOUT WRITTEN PERMISSION IS PROHIBITED.		RCK Inc Sensors and Automation Controls	3000 CAMPUS DRIVE MINNEAPOLIS, MN 55441 1-800-544-7769 (763) 553-7300 (763) 553-0708 fax turck.com	
MATERIAL		DRFT RDS	DATE 09/16/02	DESCRIPTION FS 4.4-*/1	4.5./NDT	
SEE SPECIFICATIONS	ALL DIMENSIONS DISPLAYED ON THIS	DSGN	SCALE 1=.7	rs 4,4-*/I	4.5/ NP I	
	DRAWING ARE FOR REFERENCE ONLY	UNIT OF MEASUREMENT		IDENTIFICATION NO.		
FINISH	CONTACT TURCK	MILLIMETE	ER[INCH]	DENTIFICATION NO.		
SEE SPECIFICATIONS	FOR MORE INFORMATION		•			
		DO NOT SCALE	THIS DRAWING	FILE: 777001256	SHEET 1 OF 1	