


## UL LISTED Grounding Clamp, U-Bolt, Bronze

### Type GPL

- Used to ground copper conductor parallel or at a right angle to a rod, tube, or pipe
- Made from high strength, electrolytic cast bronze
- High strength silicon bronze hardware provides long term reliable assembly
- Accommodates a wide range of pipe, tube, rod and conductor sizes – minimizes inventory requirements
- UL Listed for grounding and bonding and suitable for direct burial in earth or concrete



| Part Number | Ground Rod Size (In.) | Iron Pipe Size (In.) | Conductor Size Range | Figure Dimensions In. (mm) |                |                 | Bolt Dia. (In.) | Hex Size (In.) | Std. Pkg. Qty. |
|-------------|-----------------------|----------------------|----------------------|----------------------------|----------------|-----------------|-----------------|----------------|----------------|
|             |                       |                      |                      | L                          | W              | H               |                 |                |                |
| GPL-4-Q     | 5/8 or 3/4            | 3/8                  | #8 SOL – #4 STR      | 2.00<br>(50.8)             | 1.38<br>(35.1) | 2.75<br>(69.9)  | 3/8             | 9/16           | 25             |
| GPL-5-Q     | 5/8 or 3/4            | 3/8                  | #4 SOL – 2/0 STR     | 2.00<br>(50.8)             | 1.63<br>(41.4) | 2.75<br>(69.9)  | 3/8             | 9/16           | 25             |
| GPL-6-Q     | 5/8 or 3/4            | 3/8                  | 2/0 SOL – 250 kcmil  | 2.00<br>(50.8)             | 1.88<br>(47.8) | 2.75<br>(69.9)  | 3/8             | 9/16           | 25             |
| GPL-8-Q     | 7/8 or 1              | 1/2 or 3/4           | #8 SOL – #4 STR      | 2.38<br>(60.5)             | 1.38<br>(35.1) | 2.63<br>(66.8)  | 3/8             | 9/16           | 25             |
| GPL-9-Q     | 7/8 or 1              | 1/2 or 3/4           | #4 SOL – 2/0 STR     | 2.38<br>(60.5)             | 1.63<br>(41.4) | 2.63<br>(66.8)  | 3/8             | 9/16           | 25             |
| GPL-10-Q    | 7/8 or 1              | 1/2 or 3/4           | 2/0 SOL – 250 kcmil  | 2.38<br>(60.5)             | 1.88<br>(47.8) | 3.00<br>(76.2)  | 3/8             | 9/16           | 25             |
| GPL-14-X    | —                     | 1                    | #8 SOL – #4 STR      | 2.63<br>(66.8)             | 1.38<br>(35.1) | 2.75<br>(69.9)  | 3/8             | 9/16           | 10             |
| GPL-15-X    | —                     | 1                    | #4 SOL – 2/0 STR     | 2.63<br>(66.8)             | 1.63<br>(41.4) | 2.75<br>(69.9)  | 3/8             | 9/16           | 10             |
| GPL-16-X    | —                     | 1                    | 2/0 SOL – 250 kcmil  | 2.63<br>(66.8)             | 1.88<br>(47.8) | 3.25<br>(82)    | 3/8             | 9/16           | 10             |
| GPL-20-X    | —                     | 1 1/4                | #8 SOL – #4 STR      | 3.00<br>(76.2)             | 1.38<br>(35.1) | 3.50<br>(88.9)  | 3/8             | 9/16           | 10             |
| GPL-21-X    | —                     | 1 1/4                | #4 SOL – 2/0 STR     | 3.00<br>(76.2)             | 1.63<br>(41.4) | 3.50<br>(88.9)  | 3/8             | 9/16           | 10             |
| GPL-22-X    | —                     | 1 1/4                | 2/0 SOL – 250 kcmil  | 3.00<br>(76.2)             | 1.88<br>(47.8) | 3.50<br>(88.9)  | 3/8             | 9/16           | 10             |
| GPL-26-X    | —                     | 1 1/2                | #8 SOL – #4 STR      | 3.25<br>(82.6)             | 1.38<br>(35.1) | 4.00<br>(101.6) | 3/8             | 9/16           | 10             |
| GPL-27-X    | —                     | 1 1/2                | #4 SOL – 2/0 STR     | 3.25<br>(82.6)             | 1.63<br>(41.4) | 4.00<br>(101.6) | 3/8             | 9/16           | 10             |
| GPL-28-X    | —                     | 1 1/2                | 2/0 SOL – 250 kcmil  | 3.25<br>(82.6)             | 1.88<br>(47.8) | 4.00<br>(101.6) | 3/8             | 9/16           | 10             |
| GPL-32-3    | —                     | 2                    | #8 SOL – #4 STR      | 3.75<br>(95.3)             | 1.38<br>(35.1) | 4.25<br>(107.9) | 3/8             | 9/16           | 3              |
| GPL-33-3    | —                     | 2                    | #4 SOL – 2/0 STR     | 3.75<br>(95.3)             | 1.63<br>(41.4) | 4.25<br>(107.9) | 3/8             | 9/16           | 3              |
| GPL-34-3    | —                     | 2                    | 2/0 SOL – 250 kcmil  | 3.75<br>(95.3)             | 1.88<br>(47.8) | 4.25<br>(107.9) | 3/8             | 9/16           | 3              |
| GPL-39-3    | —                     | 2 1/2                | #4 SOL – 2/0 STR     | 4.25<br>(107.9)            | 1.63<br>(41.4) | 5.00<br>(127)   | 3/8             | 9/16           | 3              |
| GPL-40-3    | —                     | 2 1/2                | 2/0 SOL – 250 kcmil  | 4.25<br>(107.9)            | 1.88<br>(47.8) | 5.00<br>(127)   | 3/8             | 9/16           | 3              |
| GPL-44-1    | —                     | 3                    | #8 SOL – #4 STR      | 4.75<br>(120.6)            | 1.38<br>(35.1) | 5.50<br>(140)   | 3/8             | 9/16           | 1              |
| GPL-45-1    | —                     | 3                    | #4 SOL – 2/0 STR     | 4.75<br>(120.6)            | 1.63<br>(41.4) | 5.50<br>(139.7) | 3/8             | 9/16           | 1              |
| GPL-46-1    | —                     | 3                    | 2/0 SOL – 250 kcmil  | 4.75<br>(120.6)            | 1.88<br>(47.8) | 5.50<br>(139.7) | 3/8             | 9/16           | 1              |
| GPL-51-1    | —                     | 3 1/2                | #4 SOL – 2/0 STR     | 5.25<br>(133.4)            | 1.63<br>(41.4) | 6.25<br>(158.8) | 3/8             | 9/16           | 1              |
| GPL-52-1    | —                     | 3 1/2                | 2/0 SOL – 250 kcmil  | 5.25<br>(133.4)            | 1.88<br>(47.8) | 6.25<br>(158)   | 3/8             | 9/16           | 1              |
| GPL-57-1    | —                     | 4                    | #4 SOL – 2/0 STR     | 5.75<br>(146.0)            | 1.63<br>(41.4) | 6.38<br>(162.1) | 3/8             | 9/16           | 1              |
| GPL-58-1    | —                     | 4                    | 2/0 SOL – 250 kcmil  | 5.75<br>(146.0)            | 1.88<br>(47.8) | 6.38<br>(162.1) | 3/8             | 9/16           | 1              |
| GPL-75-X    | —                     | 6                    | #4 SOL – 2/0 STR     | 7.88<br>(200.2)            | 1.58<br>(40.1) | 7.85<br>(199.4) | 3/8             | 1 1/4          | 10             |