Ø22 LW Series Accessories and Replacement Parts

Accessories

Shape		Material	Type No. (Ordering Type No.)	Package Quantity	Dimensions (mm)		
Locking Ring Wrench		Nickel-plated brass	LW9Z-T1	1	Used to tighten the locking ring when installing the LW control unit onto a panel. Tightening torque: 1.2 N·m		
Lamp Holder Tool		Rubber	OR-55	1	• Used to install and remove LED lamps.		
Switch Guard	Spring Return	Guard (polyarylate) Base (polyacetal)	LW9Z-K1	1	Used to protect flush pushbuttons and illuminated pushbuttons from inadvertent operation. Degree of protection: IP65. 41.6 Panel Thickness 0.8 to 4.5 25.8		
	Maintained		LW9Z-K11	1	Note: Determine mounting centers to ensure easy operation.		
Terminal Cover For solder/tab terminal		Plastic (translucent)	LW-VL2	1	• For separate type control units only.		
Terminal Cover For screw terminal		Plastic (black)	LW-VL2M	1	• For separate type control units only.		
Terminal Cover For solder/tab terminal		Plastic (translucent)	LW-PVL	1	For unibody type pilot lights only. 19.2 7.5 988 19.2 19		
Terminal Cover For screw terminal		Plastic (translucent)	LW-PVLM	1	For unibody type pilot lights only.		
Rubber Mounting Hole Plug		Nitryl rubber (black)	OB-31PN05	5	Degree of protection: IP65 Separate		
Metal Mounting Hole Plug		Metal (diecast) Locking nut (plastic)	LW9Z-BM	1	Degree of protection: IP66 Panel thickness: 0.8 to 6 mm		

Maintenance Parts

Shape	For Use On	Material	Type No.	Ordering Type No.	Package Quantity	Color Code
Lens	Round Flush Round Flush with Square Bezel	Polyarylate	LW9Z-L1@	LW9Z-L1@PN05	5	Specify a lens color code in place of ② in the Ordering Type No. A: amber C: clear G: green R: red S: blue Y: yellow • Use the clear (C) lens for white illumination.
Lens	Round Extended	Polyarylate	LW9Z-L122	LW9Z-L12@PN05	5	
Lens	Square Flush	Polyarylate	LW9Z-L2②	LW9Z-L2@PN05	5	
Lens	ø30mm Mushroom	AS	LW9Z-L13@	LW9Z-L13@	1	