

SPECIFICATIONS

OVERVIEW

Accuracy	±2°C (±3.6°F) or ±2% of reading, for ambient temperature 10°C to 35°C (50°F to 95°F) and object temperature above 0°C (32°F)
Detector Type	Uncooled microbolometer
Field of view (FOV)	45° × 34°
IR Resolution	240 × 180 pixels
List of Contents	•Infrared camera •Hard transport case •Battery (inside camera) •USB cable •Power supply/charger with EU, UK, US and Australian plugs •Printed documentation
Multi Spectral Dynamic Imaging (MSX)	IR image enhanced with visible camera detail
Object Temperature Range	–20°C to 550°C (–4°F to 1022°F) in two ranges
Packaging Size	385 × 165 × 315 mm (15.2 × 6.5 × 12.4 in)
Thermal Sensitivity/NETD	<0.06°C (0.11°F) / <60 mK

COMPLIANCE & CERTIFICATIONS

Certifications	UL, CSA, CE, PSE and CCC
----------------	--------------------------

CONNECTIONS & COMMUNICATIONS

AC Operation	AC adapter, 90–260 VAC input, 5 VDC output to camera
Interface	USB Micro: Data transfer to and from PC and Mac device
WiFi	•Standard: 802.11 b/g/n •Frequency range: •2400–2480 MHz •5150–5260 MHz •Max. output power: 15 dBm

ENVIRONMENTAL

EMC	•WEEE 2012/19/EC •RoHS 2011/65/EC •C-Tick •EN 61000-6-3 •EN 61000-6-2 •FCC 47 CFR Part 15 Class B
Humidity (Operating and Storage)	IEC 60068-2-30/24 h 95% relative humidity

Operating Temperature Range	–15°C to 50°C (+5°F to 122°F)
Radio Spectrum	•Standard: 802.11 b/g/n •Frequency range: •2400–2480 MHz •5150–5260 MHz •Max. output power: 15 dBm
Shock	25 g (IEC 60068-2-27)
Storage Temperature Range	–40°C to 70°C (–40°F to 158°F)
Vibration	2 g (IEC 60068-2-6)
Emissivity table/correction	Emissivity table of predefined materials/variable from 0.1 to 1.0
Encapsulation/Drop	IP 54 (IEC 60529)/2m (6.6 ft.)

IMAGING & OPTICAL

Color	Black and gray
Color palettes	Black & white, iron, and rainbow
f-number	1.5
Focus	Focus free
Image Adjustment	Automatic adjust/lock image
Image Frequency	9 Hz
Image Modes	Thermal MSX, Thermal, Picture-in-Picture, Thermal blending, Digital camera.
Minimum Focus Distance	0.5 m (1.6 ft.)
Picture-in-Picture	IR area on visual image
Spatial resolution (IFOV)	3.4 mrad
Spectral Range	7.5–13 μ m
Digital Camera Resolution/FOV	640 × 480/55° × 43°

MEASUREMENT & ANALYSIS

Isotherm	Above alarm, below alarm
Reflected apparent temperature correction	Automatic, based on input of reflected temperature

Set-up Commands	Local adaptation of units, language, date and time formats
Spot Meter	Center spot; box with min./max.
Spotmeter and Area	Center spot; box with min./max.

METER DATA

Camera size (L x W x H)	244 × 95 × 140 mm (9.6 × 3.7 × 5.5 in)
Camera weight incl battery	0.575 kg (1.27 lb.)
Display	3.0 in. 320 × 240 color LCD

POWER

Charging system	Battery is charged inside the camera or in specific charger.
Charging Time	2.5 hours to 90% capacity in camera. 2 hours in charger.
Power Management	Automatic shut-down
Battery type & operating time	Rechargeable 3.6 V Li ion battery; approx. 4 hours typical use

STORAGE MEDIA

File Formats	Standard JPEG, 14-bit measurement data included
---------------------	---