	Name	Form	Language	Part no.	Article no.
Emergency stop labels					
IP66					
	Symbol (5638) for CONTROLLED STOP	Diameter = 90 mm	-	**M22-XAK-ESS**	180469
	Symbol (5638) for CONTROLLED STOP	Diameter = 60 mm	-	**M22-XBK-ESS**	180472
	Symbol (5638) for CONTROLLED STOP	33 x 50 mm	-	**M22-XZK-ESS**	180470
	Symbol (5638) for CONTROLLED STOP	33 x 50 mm	-	**M22-XZK-ESS2**	180474
	Symbol (5638) for CONTROLLED STOP	50 x 50 mm	-	**M22-XYK-ESS**	180471
Emergency-stop labels					
IP66					
		Diameter = 90 mm	de, en, fr, it	**M22-XAK1**	216465
		Diameter = 60 mm	de, en, fr, it	**M22-XBK1**	216483
NOT-AUS	NOT-AUS	33 x 50 mm	de	**M22-XZK-D99**	216471
		50 x 50 mm	de, en, fr, it	**M22-XYK1**	216484

		Rated operational voltage U_e V	Diameter d mm	Part no.	Article no.
LED-Luminous ring					
IP67, IP69K					
	Three groups of 4 LEDs each (series-connected), can be actuated separately (e.g. for continuous light)	24 V AC/DC	60 mm	**M22-XPV60-Y-24**	121477
	One group of 8 LEDs (series-connected)	120 V AC	60 mm	**M22-XPV60-Y-120**	121476
	One group of 8 LEDs (series-connected)	230 V AC	60 mm	**M22-XPV60-Y-230**	138280
Guard-ring					
IP65					
	Protection against accidental actuation	-	-	**M22-XGPV**	231273
Sealable shroud					
IP65					
	For devices with mushroom diameter 38 mm Transparent with collapse point, can be reused after Emergency-Stop, Emergency switching off operation. With grid 30 x 50 mm the drilling dimensions can be closed with M22(S)-B blanking plug	-	-	**M22-PL-PV**	216397