



1) Housing rotatable 304°, 2) Tightening torque 1...1.5 Nm, 3) Tightening torque 16.5 Nm



Display/Operation

Function indicator	yes
Power indicator	yes

Electrical connection

Connection	7/8"-16 UN-Male
Polarity reversal protected	yes
Short-circuit protection	yes

Electrical data

Magnetic field strength, interference field	100 kA/m
Min. operating current I_m	5 mA
Operating voltage U_b	20...250 VDC/20...250 VAC
Protection class	I
Rated insulation voltage U_i	250 V AC
Rated operating current I_e	500 mA
Rated operating voltage U_e AC	110 V
Rated short circuit current	100 A
Ready delay t_v max.	150 ms
Residual current I_r max.	1700 µA
Switching frequency	50 Hz
Utilization category	AC-140 DC -13
Voltage drop static max.	6 V

Inductive Sensors
BES 516-200-S2/1.500"-S5
Order Code: BHS000J



Environmental conditions

Ambient temperature	-25...70 °C
Contamination scale	3
EN 60068-2-27, Shock	Half-sinus, 30 gn, 11 ms
EN 60068-2-6, Vibration	55 Hz, amplitude 1 mm, 3x30 min
IP rating	IP67
Magnetic field immune	magnetic field immune (AC/DC)

General data

Approval/Conformity	CE cULus EAC WEEE
Basic standard	IEC 60947-5-2
Scope of delivery	O-ring Ø17.13x2.62 Allen wrench UNC 1/4"- 20x3/4"- 12.9 (2x)
Trademark	Strokemaster

Material

Gasket, material	FPM 90
Housing material	Stainless steel (1.4104) Zinc, Die casting
Material sensing surface	Ceramic
Surface protection	nickel plated

Mechanical data

Dimension	64.2 x 48 x 38.1 mm
Installation	for flush mounting
Length, tolerance	±0.05 mm
Pressure rating max.	207 bar
Pressure rating, note	oil pressure rated
Sealing ring, part number	116143
Sealing ring, size	17.13 x 2.62 mm
Size	D12.7

Output/Interface

Switching output	Normally open (NO)
------------------	--------------------

Range/Distance

Assured operating distance Sa	1.6 mm
Hysteresis H max. (% of Sr)	15.0 %
Rated operating distance Sn	2 mm
Real switching distance sr	2 mm
Repeat accuracy max. (% of Sr)	5.0 %
Temperature drift max. (% of Sr)	10 %
Tolerance Sr	±10 %

Remarks

Leakage current I_r max. at rated operating voltage U_e AC 110 V
 LED 1: Operating voltage
 LED 2: Function
 Flashing LED indicates overload. Once the overload has been eliminated, interrupt operating voltage V_s for approx. 2 sec.
 UL note:
 Listed connectors for installation are available at www.balluff.com.
 The product should be connected using a Category CYJV/7 cable having min. 95°C temperature resistance.

Connector Drawings



Wiring Diagrams

