

1) not included in scope of delivery, 2) Housing length, 3) Recommended bracket distance, 4) Null point, 5) Nominal length, 6) Mechanical null point, 7) Stroke



Display/Operation

Setting Output curve rising/falling

Electrical connection

Connection M12x1, 8-pin
 Connection version axial
 Polarity reversal protected to 36 V
 Short-circuit protection to GND and to 36 V DC

Electrical data

Current consumption max. at 24 V DC 90 mA
 Galvanic isolation yes
 Inrush current ≤ 3 A/0.5 ms
 Operating voltage U_b 18...30 VDC
 Output current max. 6 mA
 Output signal adjustable using programming inputs
 Overvoltage protection to 36 V
 Residual ripple max. 0.5 Vpp
 Switch-on delay max. 500 ms
 Voltage-proof up to (GND to housing) 500 V DC

Environmental conditions

Ambient temperature -20...85 °C
 EN 60068-2-27, Shock 100 g, 6 ms
 EN 60068-2-6, Vibration 12 g, 10...2000 Hz
 IP rating IP54 with connector
 Storage temperature -40...100 °C

Functional safety

MTTF (40 °C) 77 a

General data

Approval/Conformity CE
 cULus
 EAC
 WEEE
 Generation 1
 Version Version P1

Material

Cover material Zinc, Die-cast, nickel plated
 Housing material Aluminum
 Housing material, surface protection Anodized

Mechanical data

Housing length 325 mm
 Mounting Mounting clamps
 Stroke Length 235 mm
 Tightening torque max. 2 Nm

Output/Interface


Analog output Analog, voltage 0...10 V
 Bracket distance, recommended 205 mm
 Output characteristic linear rising/falling

Range/Distance

Measuring range	225 mm
Nominal length	225 mm
Non-linearity max.	±45 µm

Reproducibility	≤10 µm
Resolution	≤ 0.15 mV
Sampling rate typ.	32 kHz
Traverse speed max.	7 m/s

Connector Drawings



Wiring Diagrams

Pin	
1	Lb
2	0 V
3	NC
4	La
5	0...10 V
6	GND
7	+24V DC
8	NC