

Plug-in socket for RT relay Socket with logic isolation screw terminal



General technical data	
Display version LED	No
Protection class IP	IP20
Design of the switching function positively driven	No
Reference code acc. to DIN EN 81346-2	U
Design of the relay operating mechanism	poled
Product component Plug-in socket	Yes
Design of the snap-on socket base	Socket with logic isolation
Auxiliary circuit	
Number of NC contacts for auxiliary contacts	0
Number of NO contacts for auxiliary contacts	0
Number of CO contacts	0
• for auxiliary contacts	
Connections/ Terminals	
Product function	No
• removable terminal	
Type of electrical connection	screw-type terminals
Type of connectable conductor cross-sections	

• solid • finely stranded with core end processing • at AWG conductors solid	1x (1,0 ... 2,5), 2x 1,0, 2x 1,5, 2x 2,5 1x (1.0 ... 1.5), 2x 1.0, 2x 1.5 1x (18 ... 14), 2x 18, 2x 16, 2x 14
Connectable conductor cross-section • solid • finely stranded with core end processing	1 ... 2.5 mm ² 1 ... 1.5 mm ²
AWG number as coded connectable conductor cross section • solid	18 ... 14
Tightening torque • with screw-type terminals	0.5 ... 0.7 N·m

Installation/ mounting/ dimensions	
Mounting position	any
Mounting type	snap-on mounting
Height	62 mm
Width	15.5 mm
Depth	77 mm
Required spacing • with side-by-side mounting — forwards — Backwards — upwards — downwards — at the side • for grounded parts — forwards — Backwards — upwards — at the side — downwards • for live parts — forwards — Backwards — upwards — downwards — at the side	0 mm 0 mm 0 mm 0 mm 0 mm 0 mm 0 mm 0 mm 0 mm 0 mm 0 mm 0 mm 0 mm 0 mm 0 mm

Ambient conditions	
Ambient temperature • during operation • during storage • during transport	-40 ... +70 °C -20 ... +70 °C -20 ... +70 °C

Certificates/ approvals

General Product Approval

Declaration of Conformity

other



[Miscellaneous](#)

[Confirmation](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=LZS:RT78726>

Cax online generator


<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=LZS:RT78726>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/LZS:RT78726>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=LZS:RT78726&lang=en



last modified:

04/09/2020