

Pin busbar, 16 mm² connection: 2x 3-phase according to UL 489, 480Y/277V for LS 5SJ4...-HG




Figure similar

Model	
Product brand name	SETRON
Product designation	Pin busbar
Design of the product	16 mm ² , 2x3PH, UL489
General technical data	
Phase number	3
Cross-section	16 mm ²
Product details	
Product feature / insulated	Yes
Connections	
Type of electrical connection	Pin
Mechanical Design	
Width	15 mm
Length	100 mm
Net weight	66.42 g

Certificates

General Product Approval

Declaration of Conformity



UR



EG-Konf.

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5ST3665-0HG>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5ST3665-0HG>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5ST3665-0HG

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>

