

Surge suppressor, varistor, 400 ... 600 V AC, for contactors Size S2, S3



General technical data		
Product brand name		SIRIUS
Product designation		surge suppressor
Size of contactor		S2, S3
Design of the surge suppressor		with varistor
Ambient temperature		
• during storage	°C	-40 ... +80
• during operation	°C	-25 ... +60
Control circuit/ Control		
Type of voltage of the control supply voltage		AC
Control supply voltage frequency		
• 1 rated value	Hz	50
• 2 rated value	Hz	60
Control supply voltage 1		
• at AC		
— at 50 Hz	V	400 ... 600
— at 60 Hz	V	600 ... 400
Installation/ mounting/ dimensions		

Mounting position		any
Mounting type		clip-on
Width	mm	30
Height	mm	30
Depth	mm	14.5

Certificates/ approvals

Certificate of suitability	CE / UL / CSA / CCC	
General Product Approval	EMC	Declaration of Conformity
 CSA  UR  EAC  RCM  EG-Konf.	Miscellaneous	

Test Certificates	Shipping Approval	other
Type Test Certificates/Test Report   	Confirmation	

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RT2936-1BF00>

Cax online generator



<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RT2936-1BF00>


Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RT2936-1BF00>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RT2936-1BF00&lang=en





last modified:

04/09/2020