

SETRON, Switch disconnecter 3LD, main switch, 4-pole, Iu: 32 A, Operating power / at AC-23 A at 400 V: 11.5 kW, floor mounting with door coupling, rotary operating mechanism, black, central mounting 22.5 mm of the handle



Model	
Product brand name	SETRON
Product designation	3LD Switch disconnecter
Design of the product	Main switch
Display version / for switch position indicator manual operation	1 ON - 0 OFF
Design of the operating mechanism	Short rotary knob
Design of handle	rotary operating mechanism, black
Type of the driving mechanism / motor drive	No
General technical data	
Number of poles	4
Type of device	fixed mounting
Type of switch	Floor mounting with door coupling
Size of switch disconnecter	2
Electrical endurance (switching cycles)	
• at AC-23 A / at 690 V	6 000
I2t value / with closed switch / at 690 V / for combination switch + gG fuse / maximum	9 kA2.s

Let-through I _{2t} value / with closed switch / at 440 V / for combination switch + gG fuse / maximum	9 kA ² .s
Mechanical service life (switching cycles) / typical	100 000
Operating frequency / maximum	50 1/h

Voltage

Insulation voltage / rated value	690 V
Surge voltage resistance / rated value	6 kV
Operating current / at AC / rated value	32 A
Operating voltage at AC / at 50/60 Hz / rated value	690 V

Protection class

Protection class IP	IP65
Degree of protection NEMA rating	1, 3R, 4X, 12
Protection class IP / on the front	IP65

Dissipation

Power loss [W] - for rated value of the current / at AC / in hot operating state / per pole - per conductor / typical	1.8 W 1.8 W
--	----------------

Current

Operating current - at AC-23 A / at 690 V / rated value - at AC-23 A / at 400 V / rated value - at AC-22 A / at 690 V / rated value - at AC-21 / at 690 V / rated value - at AC-21 A / at 240 V / rated value - at AC-21 A / at 440 V / rated value - at AC-22 A / at 240 V / rated value - at AC-22 A / at 440 V / rated value - at AC-23 A / at 240 V / rated value - at AC-23 A / at 440 V / rated value	13 A 22 A 32 A 32 A 32 A 32 A 32 A 32 A 22 A 22 A
Operating current / of upstream fuse / rated value	40 A
Let-through current / with closed switch - at 440 V / for combination switch + gG fuse / maximum - at 690 V / for combination switch + gG fuse / maximum permissible	4.5 kA 4.5 kA
Short-time withstand current (I _{cw}) - limited to 1 s / rated value - at 690 V / limited to 1 s / rated value	640 A 640 A

Main circuit

Operating frequency	
• initial value	50 Hz
• Full-scale value	60 Hz
Operating power	
• at AC-23 A / at 240 V / rated value	6 kW
• at AC-23 A / at 400 V / at 50/60 Hz / rated value	11.5 kW
• at AC-23 A / at 400 V / rated value	11.5 kW
• at AC-23 A / at 440 V / rated value	11.5 kW
• at AC-23 A / at 690 V / rated value	11.5 kW
• at AC-3 / at 240 V / rated value	5.5 kW
• at AC-3 / at 400 V / rated value	9.5 kW
• at AC-3 / at 690 V / rated value	9.5 kW
Operating current / rated value	32 A

Auxiliary circuit	
Number of CO contacts / for auxiliary contacts	0
Number of NC contacts / for auxiliary contacts	0
Number of NO contacts / for auxiliary contacts	0
Operating voltage / of auxiliary contacts / at AC / maximum	500 V
Continuous current / of the auxiliary contact / rated value	10 A
Insulation voltage / of the auxiliary switch / rated value	500 V

Suitability	
Suitability for use	
• Main switch	Yes
• switch disconnecter	Yes
• EMERGENCY OFF switch	No
• safety switch	Yes
• maintenance/repair switch	Yes

Appearance	
Color / of the actuating element	black

Product details	
• Product function / can be locked into OFF position	Yes
Number of bracket locks / maximum	3
Hasp thickness / of the bracket locks / minimum	4 mm
Hasp thickness / of the bracket locks / maximum	8 mm
Product extension / optional	
• motor drive	No
• Voltage trigger	No

Short circuit

Conditional short-circuit current / with line-side fuse protection

- at 690 V / by gG fuse / rated value

50 kA

according UL

Operating current / at AC / acc. to UL 508 / rated value

32 A

Operating voltage / at AC / at 50/60 Hz / acc. to UL 508 / rated value

600 V

Active power [hp] / at AC / at 480 V / acc. to UL 508 / rated value

20

Active power [hp] / at AC / at 600 V / acc. to UL 508 / rated value

20

Short-time withstand current (SCCR) / at 600 V / acc. to UL 508

5 kA

Continuous current / of upstream fuse / according to UL / rated value

80 A

Type of fuse / according to UL

RK5

Number of connectable NC contacts / for auxiliary contacts / attachable / maximum

2

Number of connectable NO contacts / for auxiliary contacts / attachable / maximum

3

Number of connectable CO contacts / for auxiliary contacts / attachable / maximum

0

Connections

AWG number / as coded connectable conductor cross section / solid

- maximum
- minimum

8

14

Type of connectable conductor cross-sections / for copper conductor

- solid
- finely stranded / with core end processing
- stranded

1x (1,5...16mm²)

1x (1,5...10mm²)

1x (1,5...16mm²)

Type of connectable conductor cross-sections / for auxiliary contacts

- solid
- finely stranded / with core end processing
- stranded

lateral auxiliary switch 2x (0,75 ... 2,5mm²), 1x 4mm²; front auxiliary switch 1x (0,75 ... 2,5mm²)

lateral auxiliary switch 2x (0,75 ... 1,5mm²), 1x 2,5mm²; front auxiliary switch 1x 2,5mm²

lateral auxiliary switch 2x (0,75 ... 2,5mm²), 1x 4mm²; front auxiliary switch 1x (0,75 ... 2,5mm²)

Type of electrical connection

- for main current circuit

box terminal

- for auxiliary contacts

connection terminals

Requirements

Design of the fuse link

- for short-circuit protection of the main circuit / required
- for short-circuit protection of the auxiliary switch / required

fuse gL/gG: 40 A

fuse gL/gG: 10 A

Mechanical Design

Height

84 mm

Width

67 mm

Depth

451.5 mm

Mounting type

Built-in unit fixed-mounted version

Mounting type

- front mounting with 4-hole attachment
- front mounting with central attachment
- rail mounting

No

Yes

Yes

Net weight

455 g

Environmental conditions

Ambient temperature / during operation

- minimum
- maximum

-25 °C

55 °C

Ambient temperature / during storage / minimum

-25 °C

Certificates

Reference code

- acc. to DIN EN 61346-2
- acc. to DIN EN 81346-2

S

SF

General Product Approval

Declaration of
Conformity



CCC



CSA



UL



VDE

[Miscellaneous](#)



EG-Konf.

Test Certi-
ficates

Shipping Approval

other

[Special Test Certificate](#)



LRS



PRS

[Environmental Conformations](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3LD2244-1TL51>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3LD2244-1TL51>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)


http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3LD2244-1TL51

CAX-Online-Generator


<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



-Q1



-CI

