

Output coupler with plug-in Relay, 1 change-over contact screw terminal 230 V AC/DC Enclosure width 6.2 mm Thermal current 6A



Product brand name	SIRIUS
Product category	SIRIUS 3RQ3 coupling relays in slim design
Product designation	Coupling relays with plug-in relay
Design of the product	Output coupling link
Product type designation	3RQ3

General technical data	
Display version LED	Yes
Product component	
• Relay output	Yes
• semi-conductor output	No
Consumed active power	1 W
Insulation voltage	
• for overvoltage category III according to IEC 60664	
— with degree of pollution 3 rated value	300 V
Surge voltage resistance rated value	4 kV
maximum permissible voltage for safe isolation	
• between control and auxiliary circuit	300 V

Percental drop-out voltage related to the input voltage	10 %
Protection class IP	IP20
Shock resistance • acc. to IEC 60068-2-27	sinusoidal half-wave 15g / 11 ms
Vibration resistance • acc. to IEC 60068-2-6	6 ... 150 Hz: 2 g
Operating frequency maximum	72 000 1/h
Switching behavior	monostable
Mechanical service life (switching cycles) • typical	10 000 000
Electrical endurance (switching cycles) • at AC-15 at 230 V typical	100 000
Thermal current	6 A
Reference code acc. to DIN EN 81346-2	K

Control circuit/ Control

Control supply voltage at AC • at 50 Hz rated value • at 60 Hz rated value	230 V 230 V
Control supply voltage frequency • 1 rated value • 2 rated value	50 Hz 60 Hz
Control supply voltage at DC • rated value	230 V
Operating range factor control supply voltage rated value at DC • initial value • Full-scale value	0.8 1.1
Operating range factor control supply voltage rated value at AC at 50 Hz • initial value • Full-scale value	0.8 1.1
Operating range factor control supply voltage rated value at AC at 60 Hz • initial value • Full-scale value	0.8 1.1
Switch-on delay time • at AC maximum • at DC maximum	9 ms 8 ms
Off-delay time	19 ms
Closing delay • at AC	12 ms

• at DC	8 ms
Opening delay	
• at AC	20 ms
• at DC	18 ms
Design of the relay operating mechanism	poled
Product component Plug-in socket	Yes

Short-circuit protection

Design of the fuse link	
• for short-circuit protection of the auxiliary switch required	fuse gG: 4 A

Auxiliary circuit

Type of switching contact	Changeover contact
Material of switching contacts	AgSnO2
Number of CO contacts	
• for auxiliary contacts	1
Operating current of auxiliary contacts at AC-15	
• at 24 V	3 A
• at 250 V	3 A
Operating current of auxiliary contacts at DC-13	
• at 24 V	1 A
• at 125 V	0.2 A
• at 250 V	0.1 A
Contact reliability of auxiliary contacts	one incorrect switching operation of 100 million switching operations (17 V, 5 mA)

Main circuit

Type of voltage	AC/DC
------------------------	-------

Inputs/ Outputs

Property of the output Short-circuit proof	No
---	----

Outputs

Ampacity of the output relay at AC-15	
• at 250 V at 50/60 Hz	3 A
Ampacity of the output relay at DC-13	
• at 24 V	1 A
• at 125 V	0.2 A
• at 250 V	0.1 A

Electromagnetic compatibility

EMC emitted interference	
• acc. to IEC 60947-1	ambience A (industrial sector)
EMI immunity	
• acc. to IEC 60947-1	corresponds to degree of severity 3

Conducted interference	
• due to burst acc. to IEC 61000-4-4	2 kV
• due to conductor-earth surge acc. to IEC 61000-4-5	2 kV
• due to conductor-conductor surge acc. to IEC 61000-4-5	1 kV
Field-bound parasitic coupling acc. to IEC 61000-4-3	10 V/m
Electrostatic discharge acc. to IEC 61000-4-2	6 kV contact discharge / 8 kV air discharge

Display

Display version	
• as status display by LED	LED green

Connections/ Terminals

Product function	
• removable terminal	No
Type of electrical connection	
• for auxiliary and control current circuit	screw-type terminals
Wire length	
• at AC maximum	500 m
• at DC maximum	1 000 m
Type of connectable conductor cross-sections	
• solid	1x (0.25 ... 2.5 mm ²)
• finely stranded with core end processing	1x (0.25 ... 1.5 mm ²)
• at AWG conductors solid	1 x (20 ... 14)
Connectable conductor cross-section	
• solid	0.25 ... 2.5 mm ²
• finely stranded with core end processing	0.25 ... 1.5 mm ²
AWG number as coded connectable conductor cross section	
• solid	20 ... 14
Tightening torque	
• with screw-type terminals	0.5 ... 0.6 N·m

Installation/ mounting/ dimensions

Mounting position	any
Mounting type	snap-on mounting
Height	93 mm
Width	6.2 mm
Depth	76 mm
Required spacing	
• with side-by-side mounting	
— forwards	0 mm
— Backwards	0 mm

— upwards	0 mm
— downwards	0 mm
— at the side	0 mm
• for grounded parts	
— forwards	0 mm
— Backwards	0 mm
— upwards	0 mm
— at the side	0 mm
— downwards	0 mm
• for live parts	
— forwards	0 mm
— Backwards	0 mm
— upwards	0 mm
— downwards	0 mm
— at the side	0 mm

Ambient conditions

Installation altitude at height above sea level	
• maximum	2 000 m
Ambient temperature	
• during operation	-25 ... +60 °C
• during storage	-40 ... +85 °C
• during transport	-40 ... +85 °C
Relative humidity	
• during operation	10 ... 95 %

Certificates/ approvals

General Product Approval	EMC	Declaration of Conformity
 CCC	 EAC	 EG-Konf.
 CSA	 UL	 RCM

Declaration of Conformity	Marine / Ship-ping	other
---------------------------	--------------------	-------

[Miscellaneous](#)



[Confirmation](#)

Further information


<https://www.siemens.com/ic10>


<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RQ3118-1AF00>

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RQ3118-1AF00>

<https://support.industry.siemens.com/cs/ww/en/ps/3RQ3118-1AF00>

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RQ3118-1AF00&lang=en





last modified:

04/11/2020