

SITOR cylindrical fuse link, 22x58 mm, 20 A, aR, Un AC: 690 V, Un DC: 700 V, DC according to UL



| Model                                                                                       |                             |
|---------------------------------------------------------------------------------------------|-----------------------------|
| Product brand name                                                                          | SETRON                      |
| Product designation                                                                         | SITOR cylindrical fuse link |
| Design of the product                                                                       | DC acc. to UL               |
| General technical data                                                                      |                             |
| Operating class of the fuse link                                                            | aR                          |
| Size of the fuse link                                                                       | 22x58 mm                    |
| Type of voltage                                                                             | AC                          |
| Operating current / at AC / rated value                                                     | 20 A                        |
| Supply voltage / at DC                                                                      | 700 V                       |
| Operating voltage / rated value                                                             | 690 V                       |
| Dissipation                                                                                 |                             |
| Power loss [W] / for rated value of the current / at AC / in hot operating state / per pole | 4.6 W                       |
| Main circuit                                                                                |                             |
| Operating current                                                                           |                             |
| • Rated value                                                                               | 20 A                        |

## Product details

Product component / striker No

## Mechanical Design

Mounting position Any, preferably vertical

Net weight 50 g

## Certificates

Reference code

- acc. to DIN EN 61346-2
- acc. to DIN EN 81346-2

F

F

## General Product Approval

## Declaration of Conformity



[Miscellaneous](#)



EG-Konf.

## Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3NC2220>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3NC2220>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3NC2220](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3NC2220)

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



