

SIRIUS Compact load feeder DOL starter for IO-Link 690 V 24 V DC
0.32...1.25 A IP20 Connection main circuit: Spring-type terminal
Connection control circuit: Spring-type terminal



Product brand name	SIRIUS
Product designation	Compact starter for IO-Link
Design of the product	direct starter
Product type designation	3RA64

General technical data	
Product function	
• Control circuit interface to parallel wiring	No
Product extension	
• Auxiliary switch	Yes
Power loss [W] for rated value of the current	
• at AC in hot operating state	0.1 W
• at AC in hot operating state per pole	0.03 W
Power loss [W] for rated value of the current without load current share typical	2.9 W
Insulation voltage	
• rated value	690 V
Degree of pollution	3
Surge voltage resistance rated value	6 000 V
Protection class IP	IP20

Shock resistance	a=60 m/s ² (6g) with 10 ms per 3 shocks in all axes
Vibration resistance	f= 4 ... 5.8 Hz, d= 15 mm; f= 5.8 ... 500 Hz, a= 20 m/s ² ; 10 cycles
Mechanical service life (switching cycles)	
• of the main contacts typical	10 000 000
• of auxiliary contacts typical	10 000 000
• of the signaling contacts typical	10 000 000
Electrical endurance (switching cycles) of auxiliary contacts	
• at DC-13 at 6 A at 24 V typical	30 000
• at AC-15 at 6 A at 230 V typical	200 000
Type of assignment	continuous operation according to IEC 60947-6-2
Reference code acc. to DIN EN 81346-2	Q
Reference code acc. to DIN EN 61346-2	Q

Ambient conditions

Installation altitude at height above sea level	
• maximum	2 000 m
Ambient temperature	
• during operation	-20 ... +60 °C
• during storage	-55 ... +80 °C
• during transport	-55 ... +80 °C
Relative humidity during operation	10 ... 90 %

Main circuit

Number of poles for main current circuit	3
Adjustable pick-up value current of the current-dependent overload release	0.32 ... 1.25 A
Formula for making capacity limit current	38.4 x I _e
Formula for interruption capacity limit current	32 x I _e
Mechanical power output for 4-pole AC motor	
• at 400 V rated value	0.37 kW
• at 500 V rated value	0.55 kW
• at 690 V rated value	0.75 kW
Operating voltage	
• at AC-3 rated value maximum	690 V
Operating current	
• at AC at 400 V rated value	1.25 A
• at AC-43	
— at 400 V rated value	1.1 A
— at 500 V rated value	1.2 A
— at 690 V rated value	1.1 A
Operating power	
• at AC-3	
— at 400 V rated value	370 W

• at AC-43 — at 400 V rated value — at 500 V rated value — at 690 V rated value	370 W 550 W 750 W
No-load switching frequency	3 600 1/h
Operating frequency • at AC-41 acc. to IEC 60947-6-2 maximum • at AC-43 acc. to IEC 60947-6-2 maximum	750 1/h 250 1/h
Control circuit/ Control	
Type of voltage	DC
Holding power • at DC maximum	2.9 W
Auxiliary circuit	
Number of NC contacts for auxiliary contacts	0
Number of NO contacts for auxiliary contacts	0
Number of NO contacts • of instantaneous short-circuit trip unit for signaling contact	0
Number of CO contacts • of the current-dependent overload release for signaling contact	0
Operating current of auxiliary contacts at AC-12 maximum	10 A
Operating current of auxiliary contacts at DC-13 • at 250 V	0.27 A
Protective and monitoring functions	
Trip class	CLASS 10 and 20 adjustable
Operational short-circuit current breaking capacity (Ics) • at 400 V • at 500 V rated value • at 690 V rated value	53 kA 3 kA 3 kA
UL/CSA ratings	
Full-load current (FLA) for three-phase AC motor • at 480 V rated value • at 600 V rated value	1.25 A 1.25 A
Yielded mechanical performance [hp] • for three-phase AC motor — at 460/480 V rated value — at 575/600 V rated value	0.5 hp 0.5 hp
Short-circuit protection	

Product function Short circuit protection	Yes
Design of short-circuit protection	electromagnetic
Design of the fuse link	fuse gL/gG: 10 A
• for short-circuit protection of the auxiliary switch required	

Installation/ mounting/ dimensions	
Mounting position	any
• recommended	vertical, on horizontal standard mounting rail
Mounting type	screw and snap-on mounting
Height	191 mm
Width	45 mm
Depth	165 mm

Connections/ Terminals	
Product function	Yes
• removable terminal for main circuit • removable terminal for auxiliary and control circuit	
Type of electrical connection	spring-loaded terminals
• for main current circuit • for auxiliary and control current circuit	
Type of connectable conductor cross-sections	2x (1.5 ... 6 mm ²), 1x 10 mm ² 2x (1.5 ... 6 mm ²) 2x (1.5 ... 6 mm ²) 2x (16 ... 10), 1x 8
• for main contacts — solid — finely stranded with core end processing — finely stranded without core end processing	
• at AWG conductors for main contacts	
Type of connectable conductor cross-sections	
• for auxiliary contacts — solid — finely stranded with core end processing — finely stranded without core end processing	2x (0.25 ... 1.5 mm ²) 2x (0.25 ... 1.5 mm ²) 2x (0.25 ... 1.5 mm ²)
• at AWG conductors for auxiliary contacts	2x (24 ... 16)

Safety related data	
B10 value	3 000 000
• with high demand rate acc. to SN 31920	
Proportion of dangerous failures	50 %
• with high demand rate acc. to SN 31920	

Communication/ Protocol	
Product function Bus communication	Yes

Protocol is supported	
• IO-Link protocol	Yes
Product function Control circuit interface with IO link	Yes
IO-Link transfer rate	COM2 (38,4 kBaud)
Point-to-point cycle time between master and IO-Link device minimum	2.5 ms
Type of voltage supply via input/output link master	No
Amount of data	
• of the address area of the inputs with cyclical transfer total	2 byte
• of the address area of the outputs with cyclical transfer total	2 byte

Electromagnetic compatibility

Conducted interference	
• due to burst acc. to IEC 61000-4-4	4 kV main circuits, 2 kV auxiliary circuits, 2 kV IO-Link, 2 kV limit switches, 2 kV line hand-held device
• due to conductor-earth surge acc. to IEC 61000-4-5	4 kV main circuits, 0.5 kV auxiliary voltage with upstream overvoltage protection
• due to conductor-conductor surge acc. to IEC 61000-4-5	2 kV main circuits, 0.5 kV auxiliary voltage with upstream overvoltage protection
• due to high-frequency radiation acc. to IEC 61000-4-6	0.15-80Mhz at 10V
Field-bound parasitic coupling acc. to IEC 61000-4-3	80 ... 3000 MHz at 10V/m
Electrostatic discharge acc. to IEC 61000-4-2	8 kV
Conducted HF-interference emissions acc. to CISPR11	150 kHz ... 30 MHz Class A
Field-bound HF-interference emission acc. to CISPR11	30 ... 1000 MHz Class A

Supply voltage

Supply voltage required Auxiliary voltage	Yes
--	-----

Display

Display version	
• as status display of the input/output link device	green/red dual LED

Certificates/ approvals

General Product Approval	EMC	Functional Safety/Safety of Machinery
--------------------------	-----	---------------------------------------



Declaration of Conformity	Test Certificates	Marine / Shipping
---------------------------	-------------------	-------------------



[Miscellaneous](#)

[Type Test Certificates/Test Report](#)



Marine / Shipping	other
-------------------	-------



[Confirmation](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RA6400-2BB42>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RA6400-2BB42>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RA6400-2BB42>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RA6400-2BB42&lang=en

Characteristic: Tripping characteristics, I_t, Let-through current

<https://support.industry.siemens.com/cs/ww/en/ps/3RA6400-2BB42/char>

Further characteristics (e.g. electrical endurance, switching frequency)

<http://www.automation.siemens.com/bilddb/index.aspx?view=Search&mlfb=3RA6400-2BB42&objecttype=14&gridview=view1>

last modified:

04/07/2020