

Output coupler with plug-in Relay, 1 CO, hard gold-plated screw terminal 24 V DC Enclosure width 6.2 mm Thermal current 6A



Product brand name	SIRIUS
Product category	SIRIUS 3RQ3 coupling relays in slim design
Product designation	Coupling relays with plug-in relay
Design of the product	Output coupling link
Product type designation	3RQ3

General technical data	
Display version LED	Yes
Product component	
• Relay output	Yes
• semi-conductor output	No
Consumed active power	0.3 W
Insulation voltage	
• for overvoltage category III according to IEC 60664	
— with degree of pollution 3 rated value	300 V
Surge voltage resistance rated value	4 kV
maximum permissible voltage for safe isolation	
• between control and auxiliary circuit	300 V

Percental drop-out voltage related to the input voltage	10 %
Protection class IP	IP20
Shock resistance • acc. to IEC 60068-2-27	sinusoidal half-wave 15g / 11 ms
Vibration resistance • acc. to IEC 60068-2-6	6 ... 150 Hz: 2 g
Operating frequency maximum	72 000 1/h
Switching behavior	monostable
Mechanical service life (switching cycles) • typical	10 000 000
Electrical endurance (switching cycles) • at AC-15 at 230 V typical	100 000
Thermal current	6 A
Reference code acc. to DIN EN 81346-2	K

Control circuit/ Control

Control supply voltage at DC • rated value	24 V
Operating range factor control supply voltage rated value at DC • initial value • Full-scale value	0.8 1.25
Switch-on delay time • at DC maximum	12 ms
Off-delay time	13 ms
Closing delay • at DC	6 ms
Opening delay • at DC	13 ms
Design of the relay operating mechanism	poled
Product component Plug-in socket	Yes

Short-circuit protection

Design of the fuse link • for short-circuit protection of the auxiliary switch required	fuse gG: 4 A
---	--------------

Auxiliary circuit

Type of switching contact	Changeover contact
Material of switching contacts	AgSnO2-HTV
Number of CO contacts • for auxiliary contacts	1
Operating current of auxiliary contacts at AC-15 • at 24 V	3 A

• at 250 V	3 A
Operating current of auxiliary contacts at DC-13	
• at 24 V	1 A
• at 125 V	0.2 A
• at 250 V	0.1 A
Contact reliability of auxiliary contacts	one incorrect switching operation of 100 million switching operations (5 V, 1 mA)

Main circuit	
Type of voltage	DC

Inputs/ Outputs	
Property of the output Short-circuit proof	No

Outputs	
Ampacity of the output relay at AC-15	
• at 250 V at 50/60 Hz	3 A
Ampacity of the output relay at DC-13	
• at 24 V	1 A
• at 125 V	0.2 A
• at 250 V	0.1 A

Electromagnetic compatibility	
EMC emitted interference	
• acc. to IEC 60947-1	ambience A (industrial sector)
EMI immunity	
• acc. to IEC 60947-1	corresponds to degree of severity 3
Conducted interference	
• due to burst acc. to IEC 61000-4-4	2 kV
• due to conductor-earth surge acc. to IEC 61000-4-5	2 kV
• due to conductor-conductor surge acc. to IEC 61000-4-5	1 kV
Field-bound parasitic coupling acc. to IEC 61000-4-3	10 V/m
Electrostatic discharge acc. to IEC 61000-4-2	6 kV contact discharge / 8 kV air discharge

Display	
Display version	
• as status display by LED	LED green

Connections/ Terminals	
Product function	
• removable terminal	No
Type of electrical connection	
• for auxiliary and control current circuit	screw-type terminals
Wire length	

• at DC maximum	1 000 m
Type of connectable conductor cross-sections	
• solid	1x (0.25 ... 2.5 mm ²)
• finely stranded with core end processing	1x (0.25 ... 1.5 mm ²)
• at AWG conductors solid	1 x (20 ... 14)
Connectable conductor cross-section	
• solid	0.25 ... 2.5 mm ²
• finely stranded with core end processing	0.25 ... 1.5 mm ²
AWG number as coded connectable conductor cross section	
• solid	20 ... 14
Tightening torque	
• with screw-type terminals	0.5 ... 0.6 N·m

Installation/ mounting/ dimensions

Mounting position	any
Mounting type	snap-on mounting
Height	93 mm
Width	6.2 mm
Depth	76 mm
Required spacing	
• with side-by-side mounting	
— forwards	0 mm
— Backwards	0 mm
— upwards	0 mm
— downwards	0 mm
— at the side	0 mm
• for grounded parts	
— forwards	0 mm
— Backwards	0 mm
— upwards	0 mm
— at the side	0 mm
— downwards	0 mm
• for live parts	
— forwards	0 mm
— Backwards	0 mm
— upwards	0 mm
— downwards	0 mm
— at the side	0 mm

Ambient conditions

Installation altitude at height above sea level	
• maximum	2 000 m

Ambient temperature	
• during operation	-25 ... +60 °C
• during storage	-40 ... +85 °C
• during transport	-40 ... +85 °C
Relative humidity	
• during operation	10 ... 95 %

Certificates/ approvals

General Product Approval			EMC	Declaration of Conformity	
					
CCC	CSA	UL		RCM	EG-Konf.

Declaration of Conformity	Marine / Ship-ping	other
---------------------------	--------------------	-------

[Miscellaneous](#)



[Confirmation](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RQ3118-1AM01>

Cax online generator



<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RQ3118-1AM01>


Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RQ3118-1AM01>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RQ3118-1AM01&lang=en





last modified:

04/11/2020