

SIMATIC DP, Electronic module for ET 200 PRO 8 DI 24 V DC,
Module diagnostics; incl. bus module, Connection module IO
6ES7194-4..00-0AA0 order separately



General information	
Product function	
• Isochronous mode	No
Supply voltage	
Rated value (DC)	24 V
Reverse polarity protection	Yes; Against destruction; encoder power supply outputs applied with reversed polarity
Input current	
from supply voltage 1L+, max.	20 mA
from backplane bus 3.3 V DC, max.	20 mA
Encoder supply	
Number of outputs	8
Short-circuit protection	Yes; per module, electronic
Output current	
• up to 55 °C, max.	1 A
Power loss	
Power loss, typ.	2.5 W

Address area	
Address space per module	
• Address space per module, max.	1 byte
Digital inputs	
Number of digital inputs	8
Input characteristic curve in accordance with IEC 61131, type 1	Yes
Input characteristic curve in accordance with IEC 61131, type 2	No
Number of simultaneously controllable inputs	
all mounting positions	
— up to 55 °C, max.	8
Input voltage	
• Rated value (DC)	24 V
• for signal "0"	-3 to +5V
• for signal "1"	13 to 30V
Input current	
• for signal "1", typ.	7 mA
Input delay (for rated value of input voltage)	
for standard inputs	
— parameterizable	No
— at "0" to "1", min.	1.2 ms
— at "0" to "1", max.	4.8 ms
— at "1" to "0", min.	1.2 ms
— at "1" to "0", max.	4.8 ms
Cable length	
• unshielded, max.	30 m
Encoder	
Connectable encoders	
• 2-wire sensor	Yes
— permissible quiescent current (2-wire sensor), max.	1.5 mA
Interrupts/diagnostics/status information	
Diagnostics function	Yes
Alarms	
• Diagnostic alarm	Yes
Diagnostic messages	
• Diagnostic information readable	Yes
• Short-circuit	Yes; Sensor supply to M; module by module
Diagnostics indication LED	
• Group error SF (red)	Yes

- Status indicator digital input (green)

Yes; Per channel

Potential separation

between backplane bus and all other circuit components

Yes

Potential separation digital inputs

- between the channels
- between the channels and backplane bus

No

Yes

Isolation

Isolation tested with

707 V DC (type test)

Dimensions

Width

45 mm

Height

130 mm

Depth

35 mm

Weights

Weight, approx.

140 g

last modified:

05/06/2020