

Switch disconnecter in new design Iu=63 A, Ue = 690 V, 3-pole with door drive 8UC7 Handle dark blue/blue-green Basic masking frame light gray



Figure similar

Model	
Product brand name	SETRON
Product designation	Switch Disconnecter 3KA
Design type	For mounting and installation
Design of the operating mechanism	manual operating mechanism
Design of the load switch / Strip form	No
Type of the driving mechanism / motor drive	No
Type of device	fixed mounting
Protection against electrical shock	finger-safe
Insulation voltage / rated value	690 V
Type of voltage	AC/DC
Operating voltage	
• at AC / at 50/60 Hz / rated value	690 V
• at DC / rated value	440 V
Protection class	
Protection class IP	IP00
Dissipation	

Power loss [W] / for rated value of the current / at AC / in hot operating state / per pole	2.33 W
Current	
Let-through current / I _{2 t} / maximum permissible / in utilization category / AC-22 B / at 400 V	24 000 A ² ·s
Main circuit	
Number of poles / for main current circuit	3
Operating power	
• at AC-23 A / at 400 V / at 50/60 Hz / rated value	30 000 W
• at AC-23 A / at 400 V / rated value	30 000 W
• at AC-23 A / at 500 V / rated value	30 000 W
• at AC-23 A / at 690 V / at 50/60 Hz / rated value	40 000 W
Operating current / rated value	63 A
Rated current I _e / maximum / in utilization category	
• AC-21 A / at 400 V	63 A
• AC-21 A / at 500 V	63 A
• AC-21 B / at 400 V	63 A
• AC-21 B / at 500 V	63 A
• AC-22 A / at 400 V	63 A
• AC-22 A / at 500 V	63 A
• AC-22 B / at 400 V	63 A
• AC-22 B / at 500 V	63 A
Auxiliary circuit	
Number of CO contacts / for auxiliary contacts	0
Number of NC contacts / for auxiliary contacts	0
Number of NO contacts / for auxiliary contacts	0
Short circuit	
Maximum short-circuit current breaking capacity (I _{cu}) / at 400 V / rated value	50 kA
Conditional rated short-circuit current	
• 400V	120 kA
• 500V	120 kA
• in utilization category / AC-21 A / at 400 V	120 kA
• in utilization category / AC-21 A / at 500 V	120 kA
• in utilization category / AC-21 B / at 400 V	120 kA
• in utilization category / AC-21 B / at 500 V	120 kA
• in utilization category / AC-22 A / at 400 V	120 kA
• in utilization category / AC-22 A / at 500 V	120 kA
• in utilization category / AC-22 B / at 400 V	120 kA
• in utilization category / AC-22 B / at 500 V	120 kA

Connections

Connectable conductor cross-section / for main contacts	
• stranded / maximum	35 mm ²
Type of connection, main circuit	Flat-type screw terminal
Type of electrical connection	
• for main current circuit	flat connector

Mechanical Design

Height	105 mm
Width	120 mm
Depth	150 mm
Type of mounting	fixed mounted
Mounting type	floor mounting
Mounting type	
• front mounting with 4-hole attachment	No
• front mounting with central attachment	No
• rail mounting	No
Mounting position	any
Net weight	1.372 kg

Environmental conditions

Ambient temperature / during operation	
• minimum	-25 °C
• maximum	55 °C
Ambient temperature / during storage	
• minimum	-50 °C
• maximum	80 °C

Certificates

Reference code	
• acc. to DIN EN 61346-2	Q
• acc. to DIN EN 81346-2	Q

Declaration of Conformity	Test Certificates	Shipping Approval	other
---------------------------	-------------------	-------------------	-------



[Special Test Certificate](#)



[Miscellaneous](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3KA5030-1GE01>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3KA5030-1GE01>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3KA5030-1GE01

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>