

busbar adapter 60 mm SYS. UL 508 Busbar system 60 mm Bar thickness: TT profile UL rating 240-600V/250A Can be used in spring circuits IEC rating 690 V/250 A for 3VL circuit breaker with pipe contacting for cable outlet top/bottom Adapter length 190 mm Adapter width 105 mm for VL150 UL DG-FRAME for VL250 UL FG-FRAME



Model	
Product brand name	SETRON
Product designation	Device adapter
Design of the product	Accessories
Operating current / at AC / rated value	250 A
Operating voltage / at AC / rated value	690 V
Suitability for use	3VL150 UL DG FRAME and 3VL250 UL FG FRAME

Connections	
Type of connectable conductor cross-sections / for copper conductor / stranded	Tubular contacts

Mechanical Design	
Width	105 mm
Length	190 mm
Busbar center-to-center spacing	60 mm
Net weight	969 g

Certificates	
--------------	--

General Product Approval			Declaration of Conformity	Test Certificates
 CSA	 UR	 UL	 EAC	 EG-Konf.

[Special Test Certificate](#)

Test Certificates	Shipping Approval		other
Miscellaneous	 ABS	 PRS	 RINA

[Miscellaneous](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=8US1213-4AQ03>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/8US1213-4AQ03>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8US1213-4AQ03

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>

