

SITOR fuse link, with slotted blade contacts, NH2, In: 710 A, aR, Un
AC: 800 V, Un DC: 440 V, front indicator



Model	
Product brand name	SETRON
Product designation	SITOR fuse link
Design of the product	With slotted blade contacts
Design of an identification indicator	front indicator
Design of the switching contact	With blade contacts, silver-plated
Design of the fuse link	SITOR, LV HRC design
General technical data	
Size of fuse system / acc. to DIN EN 60269-1	NH2
Operating class of the fuse link	aR
Varying load factor (WL)	0.85
Supply voltage	
Type of voltage	AC/DC
Operating current / at AC / rated value	710 A
Supply voltage	
• at AC / rated value	800 V
• at DC	440 V
Switching capacity	

Switching capacity current		
• acc. to IEC 60947-2 / rated value	100 kA	
Dissipation		
Power loss [W]	155 W	
Power loss [W]		
• for rated value of the current / at AC / in hot operating state / per pole	155 W	
• maximum	155 W	
Product details		
Product description	Not non-interchangeable	
Mechanical Design		
Mounting position	Any, preferably vertical	
Environmental conditions		
Ambient temperature		
• minimum	-20 °C	
• maximum	50 °C	
Environmental category	-20 to +50 at 95% relative humidity	
Certificates		
Reference code		
• acc. to DIN EN 61346-2	F	
• acc. to DIN EN 81346-2	F	
Declaration of Conformity	Test Certificates	other



[Special Test Certificate](#)

[Miscellaneous](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3NE4337>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3NE4337>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3NE4337

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



