

SIMATIC DP, Electronics module ET200S: 2AI High Speed I-2-wire 0-20 mA; 4.. 20mA, 15 bit, 15 mm width, for 2-wire transducer Cycle time of module: 0.1 ms, with SF LED (group fault)



Figure similar

Supply voltage		
Load voltage L+		
• Rated value (DC)	24 V	
• Short-circuit protection	Yes	
• Reverse polarity protection	Yes	
Input current		
from load voltage L+ (without load), max.	225 mA	
from backplane bus 3.3 V DC, max.	10 mA	
Output voltage		
Power supply to the transmitters		
• present	Yes	
Power loss		
Power loss, typ.	2.5 W	
Address area		
Address space per module		

• Address space per module, max.	4 byte
Analog inputs	
Number of analog inputs	2
Cycle time (all channels) max.	0.25 ms
Input ranges (rated values), currents	
• 0 to 20 mA	Yes
— Input resistance (0 to 20 mA)	106 Ω
• 4 mA to 20 mA	Yes
Cable length	
• shielded, max.	200 m
Analog value generation for the inputs	
Integration and conversion time/resolution per channel	
• Resolution with overrange (bit including sign), max.	16 bit
Encoder	
Connection of signal encoders	
• for current measurement as 2-wire transducer	Yes
Errors/accuracies	
Operational error limit in overall temperature range	
• Current, relative to input range, (+/-)	0.3 %
Basic error limit (operational limit at 25 °C)	
• Current, relative to input range, (+/-)	0.2 %
Interrupts/diagnostics/status information	
Alarms	
• Hardware interrupt	Yes
Diagnostic messages	
• Wire-break	Yes; at 4 to 20 mA
• Group error	Yes
• Overflow/underflow	Yes
Diagnostics indication LED	
• Group error SF (red)	Yes
Parameter	
Diagnostics wire break	At 4 to 20 mA
Measurement type/range	4 to 20 mA, 0 to 20 mA
Group diagnostics	1
Overflow/underflow	1
Potential separation	
Potential separation analog inputs	
• between the channels	No
• between the channels and backplane bus	Yes

- Between the channels and load voltage L+

Yes

Dimensions

Width	15 mm
Height	81 mm
Depth	52 mm

last modified:

05/06/2020