

SITOR fuse link, with female thread on both sides, In: 710 A, gR, Un
AC: 900 V, front indicator



Model	
Product brand name	SETRON
Product designation	SITOR fuse link
Design of the product	With female thread on both sides
Design of an identification indicator	front indicator
Design of the fuse link	Fuses for special applications
General technical data	
Size of fuse system / acc. to DIN EN 60269-1	others
Operating class of the fuse link	gR
Varying load factor (WL)	0.9
Supply voltage	
Type of voltage	AC
Operating current / at AC / rated value	710 A
Supply voltage	
• at AC / rated value	900 V
Switching capacity	
Switching capacity current	
• acc. to IEC 60947-2 / rated value	100 kA

Dissipation	
Power loss [W]	150 W
Power loss [W]	
• for rated value of the current / at AC / in hot operating state / per pole	150 W
• maximum	150 W
Product details	
Product description	Not non-interchangeable
Mechanical Design	
Mounting position	Any, preferably vertical
Environmental conditions	
Ambient temperature	
• minimum	-20 °C
• maximum	50 °C
Environmental category	-20 to +50 at 95% relative humidity
Certificates	
Reference code	
• acc. to DIN EN 61346-2	F
• acc. to DIN EN 81346-2	F
Test Certificates	other
Special Test Certificate	Miscellaneous

Further information
Information- and Downloadcenter (Catalogs, Brochures,...) http://www.siemens.com/lowvoltage/catalogs
Industry Mall (Online ordering system) https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3NE6437
Service&Support (Manuals, Certificates, Characteristics, FAQs,...) https://support.industry.siemens.com/cs/ww/en/ps/3NE6437
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...) http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3NE6437
CAX-Online-Generator http://www.siemens.com/cax
Tender specifications http://www.siemens.com/specifications

