

Connection terminal set, 3-pole for flat bars to 32x 20 mm Busbar center-to-center spacing 60 mm UL 508A *** Cover 8US1922-1GC00 to be ordered separately ***



Model	
Product brand name	SETRON
Product designation	Connecting terminal
Design of the product	Accessories
Operating current / at AC / rated value	800 A
Suitability for use	Flat bars up to 32 x 20 mm
Product feature / halogen-free	Yes
Connections	
Type of connectable conductor cross-sections / for copper conductor / stranded	32 mm x 20 mm
Mechanical Design	
Busbar center-to-center spacing	60 mm
Net weight	1 339 g
Certificates	

General Product Approval				Declaration of Conformity	Test Certific- ates
 CSA	 UR	 UL		 EG-Konf.	Special Test Certificate

Test Certific- ates	Shipping Approval		other
Miscellaneous	 PRS	 RINA	Miscellaneous

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=8US1941-2AA04>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/8US1941-2AA04>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8US1941-2AA04

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>

