

Fault signal contact 2 NO, for miniature circuit breaker according to UL 489



Model	
Product brand name	SENTRON
Product designation	Fault signal contact
Design of the product	Mountable
Electrical endurance (switching cycles) / typical	12 000
Voltage	
Insulation voltage / rated value	440 V
Surge voltage resistance / rated value	4 kV
Supply voltage	
Operating frequency	50/60 Hz
Protection class IP	IP20
Product details	
Product component	
• fault signal contact	Yes
Number of fault signal contacts	1
Number of NC contacts	0
Number of NO contacts	2
Number of CO contacts	0

Product extension	Fault signal contact
-------------------	----------------------

Connections

Connectable conductor cross-section	
• minimum	0.5 mm ²
• maximum	2.5 mm ²
Tightening torque / with screw-type terminals	
• maximum	0.5 N·m
Type of connectable conductor cross-sections / at AWG conductors	24 ... 12

Mechanical Design

Height	110 mm
Width	9 mm
Depth	70 mm
Net weight	85 g

Certificates

General Product Approval



Declaration of Conformity

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5ST3021-0HG>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5ST3021-0HG>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5ST3021-0HG

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



